

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/-
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED NEW MEXICO OIL CONSERVATION COMMISSION

SEP 26 1967

O. O. O.
REGISTRATION OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator H. N. Sweeney	8. Farm or Lease Name O'Brien "B"
3. Address of Operator Box 1582 - Roswell, New Mexico 88201	9. Well No. 2
4. Location of Well UNIT LETTER J , 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 9S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Indes. Twin Lakes-S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3949' GR	12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> <i>Sq. Pay + Treat</i>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out to 2704', set bridging plug at 2670'. Perforated 2622-2666 with 10 shots. Set cement retainer 2603'. Squeezed with 100 sacks. Final squeeze pressure 2200#. Perforated 10 shots from 2672-76 and 2684-90. Treated with 3000 gallons 28% acid. After recovering lead well swabbed 4 BPPH (50% oil - 50% water).
2572-76 2584-96

Rigging w/ pumping unit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Martha J. West</u>	TITLE <u>Clerk</u>	DATE <u>9-25-67</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>SEP 26 1967</u>

CONDITIONS OF APPROVAL, IF ANY: