

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Dr. Sam G. Dunn</u>		Lease <u>Penbergross</u>		Well # <u>3</u>	
Location of Well	Unit <u>330 N 330 E</u> <u>A</u>	Section <u>5</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>H. E. Bremer</u>		Type of Equipment <u>Rotary</u>		

  

APPROVED CASING PROGRAM

*Approved 12-6-63 1100 SA*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 7/8</u>	<u>32 #</u>	<u>used</u>	<u>100</u>	<u>Circulate</u>
<u>6 3/4</u>	<u>4 1/2</u>	<u>9 1/2</u>	<u>new</u>	<u>1100</u>	<u>50 sacks</u>

  

Casing Data: 6 3/4 joints of 4 1/2 inch # Grade 40 but cement 5-8 ft. in  
4 used (Approved) (Rejected)

Inspected by   date 6-12-63

Cementing Program

Size of hole 6 3/4 Size of Casing   Sacks cement required  

Type of Shoe used   Float collar used   Btm 3 jts welded  

TD of hole 1025 Set   Feet of   Inch   # Grade  

New-used csg. @   with   sacks neat cement around shoe

+   sax   additives  

Plug down @   (AM) (PM) Date  

Cement circulated   No. of Sacks  

Cemented by H. E. Bremer Witnessed by  

Temp. Survey ran @ 7:30 (AM) (PM) Date 6-12-63 top cement @ 1025

Casing test @   (AM) (PM) Date  

Method Used   Witnessed by  

Checked for shut off @   (AM) (PM) Date  

Method used   Witnessed by  

Remarks: 3 1/2" casing 100' depth 5-8 ft. in  
1100' depth 5-8 ft. in