

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 60 feet to 2202 feet, and from 0 feet to 60 feet.
Cable tools were used from 0 feet to 60 feet, and from 60 feet to 2202 feet.

PRODUCTION

Put to Producing Dry Hole, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian.	T. Ojo Alamo.
T. Salt.	T. Silurian.	T. Kirtland-Fruitland.
B. Salt.	T. Montoya.	T. Farmington.
T. Yates. 305	T. Simpson.	T. Pictured Cliffs.
T. 7 Rivers. 400	T. McKee.	T. Menefee.
T. Queen. 895	T. Ellenburger.	T. Point Lookout.
T. Grayburg.	T. Gr. Wash.	T. Mancos.
T. San Andres. 1390	T. Granite.	T. Dakota.
T. Glorieta.	T.	T. Morrison.
T. Drinkard.	T.	T. Penn.
T. Tubbs.	T.	T.
T. Abo.	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Cored, 1970	1970	2022	rec. 51 feet (Slaughter Zone of San Andres dolomite, dense, anhydritic, no show				
1970	1974		dolomite, anhydritic, pinpoint porosity, fair show				
1974	1975 1/2		dolomite, anhydritic, dense, v/slight fractures & slight bleeding				
1975 1/2	1986		dolomite, anhydritic, poor to fair show, slight fracturing and pinpoint to vuggy porosity				
1986	1991		dolomite, dense, with faint scattering show in fracture poros				
1991	1997		dolomite, dense no show				
1997	2003		dolomite, fractured, w/pinpoint porosity, good show				
2003	2009		dolomite, dense, w/some fractures bleeding water				
2009	2018		dolomite, fair porosity, poor show of bleeding heavy oil w/salt water				
2018	2021						
Cored, 2022	2074		rec. 52 feet.				
2022	2048		dolomite, fair porosity, bleeding salt water w/traces oil				
2048	2074		dolomite, dense				
Core Lab Analysis run 1974 - 1975 1/2, 1986 - 1987 1/2, 1989 - 1991, 2003 - 2009'							
Schlumberger Borehole Compensated Sonic-Gamma Ray, Laterolog and Microlaterolog run to T.D.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 22, 1966

(Date)

Company or Operator Roy H. Smith Drilling Co.

Address 728 1st. Wichita National Bldg.

Name Betty Weeford

Wichita Falls, Texas

Position or Title Secretary