

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Artesia, NM 88210

NM OIL GASES & MINES  
(Other Instructions)

SECTION

BLM-1004-0135  
Expires August 31, 1985

2151

SUNDRY NOTICES AND REPORTS RECEIVED BY

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

AUG 01 1985

O. C. D.

ARTESIA, OFFICE

6. LEASE DESIGNATION AND SERIAL NO.

LC 067811

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nichols Dale Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Pecos San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-7-S, R-26-E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Stevens Operating Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2203 Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface 1650 FNL, 990 FEL, Sec. 33, T-7-S, R-26-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, OR, etc.)

3753 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Set WLBP @ 1200' + 40' Cement Cap.
2. 4 1/2 casing Free Point @ 240'.
3. Perforated 4 shots @ 240' and circ cement to surface outside and inside 4 1/2 casing with 80 sxs class "C" 2% CaCl<sub>2</sub> cement.
4. Set dry hole marker.

Best ID-2  
11-16-84  
P+R

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Controller

DATE 9-25-84

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED  
PETER W. CHESTER

JUL 30 1985

BUREAU OF LAND MANAGEMENT  
RESOURCE AREA

\*See Instructions on Reverse Side