DISTRI	· · · · · · · · · · · · · · · · · · ·		Form C-193
	HOITUBI		Supersedes Old
SANTA FE		RECEINED CAPIL CONSERVATION COMM	C-102 and C-103 Effective 1-1-65
FILE	VV		Ettection 1-1-92
U.S.G.S.		1100 00 111110	5a. Indicate Type of Luase
LAND OFF	ICF I	MAR 06 1986	
OPERATOR			State Fee
		O. C. D.	5. State Oil & Gas Lease No.
		ARTESIA, OFFICE	
(D0 w	SUNDRY	THE PARTY OF THE P	
<del></del>	USE TAPPLICATION	NOTICES AND REPORTS ON WELLS  ISALS TO DRILL OR TO DEEPEN OR PLUG SACK TO A DIFFERENT IN FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	RESERVOIR.
OIL	~ sas [		7. Unit Agreement Name
writ		OTHER. Water Disposal	
i. Name of Cp			. 8. Farm or Lease Name
McClel	lan Oil Corporati	on.	
. Address of	Operator		G.F. Bannon, et a
P.O. D	rawer 730, Roswel	1. NM 88202	9. Well No.
. Location of	W•11		1
	P . 660	<b>9</b> -11	10. Field and Pool, or Wildcat
0417 6677		FEET FROM THE SOUTH LINE AND 660	Haystack
	+	1 m ·	THINITING THE STATE OF THE STAT
East	LINE, SECTION	15 TOWNSHIP 6-S NANGE 27	-E (
mm	mmmmin		
[[[[]]]		15. Elevation (Show whether DF, RT, GR, etc.)	
7177777		4053' K.B.	12. County Chaves
•	Check Apr	propriate Box To Indicate Nature of Notice,	Chaves
	NOTICE OF INTE	ENTION TO:	Report or Other Data
			SUBSEQUENT REPORT OF:
	DIAL WORK		· · · · · · · · · · · · · · · · · · ·
L W PORARILY A		PLUG AND ABANDON REMEDIAL WORK	1.55
ULL 0+ ALTER		COMMENCE DRILLING	OPHS.
		CHANGE PLANS CASING TEST AND CE	
01-1-	••	OTHER	
. Describe Pr	roposed or Completed Operati	long (Class)	
. Describe Pr work) see	roposed or Completed Operati RULE 1701.	ions (Clearly state all pertinent details, and give pertinen	t dates, including estimated days
Describe Pr work) see	roposed or Completed Operation	ions (Clearly state all pertinent details, and give pertinen	t dates, including estimated date of starting any pro
Describe Pr work) see	riowed well down	1. Dug out bradonhand	
Describe Pr work) see 1/22/86	previously. Set	Dug out bradenhead which had bee	en "ready-mixed"
Describe Pr work) see 1/22/86	previously. Set shoe at 1,403'.	Dug out bradenhead which had bee	en "ready-mixed"
. Peccribe Pr work) see 1/22/86	previously. Set	1. Dug out bradonhand	en "ready-mixed"
1/22/00	previously. Set shoe at 1,403'. overnight.	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with	en "ready-mixed" plug across 8-5/8" wireline. Left
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with	en "ready-mixed" plug across 8-5/8" wireline. Left
. Describe Pr work) see 1/22/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left Squeezed 120 sx
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	en "ready-mixed" plug across 8-5/8" wireline. Left  Squeezed 120 sx Held 1,500 psi.
1/22/00	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" case class "C" w/2% Case	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	Post \$\pm\$ 10-2
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post TD-2
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post TD-2
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post TD-2
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl2 cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes.	Post TD-2
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post to -2  3-14-86 PHA
1/22/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post to -2  3-14-86 PH.
1/23/86	previously. Set shoe at 1,403'. overnight.  Perfed 8-5/8" car class "C" w/2% Carlotter for the control of the c	Dug out bradenhead which had been 150 sx class "C" w/2% CaCl <sub>2</sub> cement Tagged top of plug at 1,250' with sing at 200' with 3 squeeze holes. aCl <sub>2</sub> into perfs and 8-5/8" casing. le marker.	Post to -2  3-14-86 PY-A