

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

Clinton C. Hayes

(C) 1960

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>C. C. Hayes</i>		Lease <i>Item 11</i>		Well # <i>1</i>	
Location of Well	Unit <i>2050-5600</i>	Section <i>20</i>	Township <i>12</i>	Range <i>26</i>	County <i>Chavez</i>
Drilling Contractor <i>Southwest Drilling Co.</i>			Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

5600 ft. casing program approved 5-27-60

12 3/4" hole 400 ft. casing, 12 3/4" hole 200 ft. casing, 8 5/8" hole 5600 ft. casing.

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>12 3/4"</i>	<i>13 3/8"</i>	<i>25"</i>		<i>450</i>	<i>200</i>
<i>11 7/8"</i>	<i>8 5/8"</i>	<i>24"</i>		<i>2200</i>	<i>100</i>
<i>7 7/8"</i>	<i>5 1/2"</i>	<i>15.5"</i>		<i>5600</i>	<i>200</i>

Casing Data:

Surface *62* joints of *8 5/8* inch *24* # Grade *New J 55* (Approved) (~~Rejected~~)

Inspected by *Gressett* date *6-8-60*

Cementing Program

Size of hole *11* Size of Casing *8 5/8* Sacks cement required

Type of Shoe used *Line* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *2200* Set *200* Feet of *8 5/8* Inch *24* # Grade *new*

New ~~used~~ csg. @ *2199* with *200* sacks neat cement around shoe
+ *700* sax *Super Cement* additives

Plug down @ *9:45* (AM) (PM) Date *6-8-60*

Cement circulated *yes* No. of Sacks *approved*

Cemented by *Clinton C. Hayes* Witnessed by *Gressett*

Temp. Survey ran @ *11:00* (AM) (PM) Date *6-8-60* top cement @ *150* ft.

Casing test @ *1000* (AM) (PM) Date

Method Used *1000* Witnessed by

Checked for shut off @ *1000* (AM) (PM) Date

Method used *1000* Witnessed by

Remarks: *Cement test failed and was within 10 minutes after*

plug set down to run survey 7:00 PM. 6-8-60

2.2.60