

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-005-10513

Indicate Type of Lease

STATE ☒

FEE ☐

State Oil & Gas Lease No.
E-3614

Lease Name or Unit Agreement Name
Standard State

Well No.
6Y

Pool name or Wildcat
ACME (San Andres)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

Name of Operator
N. Dale Nichols

Address of Operator
P.O. Box 1972, Midland, Texas 79702

Well Location

Unit Letter G : 2310 Feet From The North Line and 2310 Feet From The East Line

Section 5 Township 8S Range 27E NMPM Chaves County

Elevation (Show whether DF, RKB, RT, GR, etc.)
3977

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) 5-29-02 RU company pulling with 3 7/8" bit 1 3 1/8" bottom collar with reverse unit. Drilled rust and scale out of bad casing 10' - 68'. Washed to 375' hit parted casing. Had very hard time getting bit through parted casing. Washed to 1908' hit iron in hole could go no futher. While washing out the 4 1/2" casing at surface fell down hole 18" until tubing slips were setting on the 8 5/8" surface casing. At this point we called Van Barton at the Artesia OCD office and got verbale apporval to plug the well.
- 2) 5-30-02 Pump 38 sks of cement at 1908', pulled tubing to 900'.
- 3) 5-31-02 run tubing back and tagged cement at 1320'. Pulled tubing to 403' pumped 25 sks cement and pulled out of hole.
- 4) 6-3-02 Ran tubing open ended and taged cement 222'. Mixed 25 sks cement and filled hole and annulas between 4 1/2" and 8 5/8" to surface. Installed Dry hole marker and cleaned up location. Well is P & A

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John E. Nichols TITLE Manager

DATE 06-12-2002

TYPE OR PRINT NAME John E. Nichols

TELEPHONE NO. 915-697-1576

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

DEC 17 2002