

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

NM000 - ARTEZIA

NM000 - HOOBBS

BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
OCT 7 1966

2. NAME OF OPERATOR
Grover, MacCurdy and Hoffacker

3. ADDRESS OF OPERATOR
306 Midland National Bank Building, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' PNL & 660' FWL of Section 24

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4005 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 0266414

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Strange-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 24, T9S, R29E

12. COUNTY OR PARISH
Chaves

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well drilled to 3350' in lime. Ran DST No. 1 from 3210' to 3350'. Tool open 60 min.

Recovered 375' muddy saltwater. No shows of oil or gas.

Reason for abandonment - no commercially producible hydro carbons present.

Formation Tops: Yates - 1320'

San Andres - 2510'

Pi Marker - 3036'

Slaughter Interval - 3195' to 3255'

P-1 3230' - 3250'

Other porous zones - 3295' to 3310'

Cement plugs to be placed thru drill pipe by Halliburton Oil Well Cementing Co. as follows:

205' plug from 3175' to 3325'

50' plug from 375' to 425'

5 sack plug at the surface.

Heavy mud to be placed between cement plugs. 397' of 8 5/8" surface casing to remain in well and marked with a pipe monument extending 4' above ground level with well number and location. Verbal approval of abandonment program received from Mr. Ed Wyatt, Engineer, USGS.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Partner

DATE

9-28-66

(This space for Federal or State office use)

APPROVED

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 6 1966

J. W. SUTHERLAND

DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.