

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/-
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole		7. Unit Agreement Name	
2. Name of Operator Cities Service Oil Company		8. Farm or Lease Name O'Brien B	
3. Address of Operator Box 69, Hobbs, New Mexico 88240		9. Well No. 1	
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 7 South RANGE 29 East N.M.P.M.		10. Field and Pool, or Wildcat Wildcat	
15. Elevation (Show whether DF, RT, GR, etc.) 4400' G.L.		12. County Chaves	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug and abandon the subject well in the following manner:

1. Load hole with mud laden fluid.
2. Set 25 sack cement plug across top of Glorietta @ 3526'.
3. Set 30 sack plug across top porosity zone of the San Andres "A" @ 2867'
4. Set 30 sack plug across top of Queen at 1748'.
5. Set 30 sack plug half in and half out of 8 5/8" at approximately 177-267.
6. Set 10 sack cement surface plug w/4" marker extending 4' above ground to designate a P & A location.
7. Clean location of all equipment and debris and fill pits and cellar.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Clifford W. Robertson</u>	TITLE District Clerk	DATE 11-17-66
PROVED BY <u>W. A. Grissitt</u>	TITLE <u>ASSISTANT</u>	DATE 11-17-66
ADDITIONS OF APPROVAL, IF ANY:		