

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
3. Address of Operator ELK OIL COMPANY	9. Well No. STATE "OBK"
4. Location of Well BOX 310 ROSWELL, NEW MEXICO 88201	10. Field and Pool, or Wildcat
UNIT LETTER A 660 FEET FROM THE NORTH LINE AND 660 FEET FROM THE EAST LINE, SECTION 16 TOWNSHIP 8-S RANGE 28-E NMPM.	WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.) 4013 GR	12. County CHAVES

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 2691 feet.
8 5/8" casing cemented at 790' with 100 sax
4 1/2" casing cemented at 2690' with 300 sax
Perforated 8 perfs. 2609'-2617'
Acidized 2000 Gals
Swabbed Dry
Set Baker Bridge plug at 2590'
Perforated 5 Perfs 2549'-2571'
Acidized 3000 Gals
Swabbed Dry
Set Baker Bridge plug at 2540'
Perforated 10 perfs 2461'-2509'
Acidized 3000 Gals
Frac treated 20000 Gals 20000 # sand
Pumped 1 BBL oil 40 BBW water /

Will set plug of 25 sax at
2400-2450 pull approximately.
1200 ft 4 1/2" casing
Set plug 1200-1250 with 25 sax.
Set plug 750-790' in 8 5/8 with 25 sax.
Set surface plug 0-50' with 25 sax.
Place marker and level pits.

RECEIVED

MAR 14 1967

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John M. Kelly TITLE Consultant DATE Mar. 10, 1967
APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE 1967
CONDITIONS OF APPROVAL, IF ANY: