

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR. DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

NMOCC - ARIZONA
NMOCC - HOUSTON
BLM - SANTA FE

SUMMARY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Midwest Oil Corporation		8. FARM OR LEASE NAME Atlantic Federal	
3. ADDRESS OF OPERATOR 1500 Wilco Building, Midland, Texas		9. WELL NO. 91	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660 PSL and 660 PSL		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC 10, T-10-S, R-29-E	
15. ELEVATIONS (Show whether of, ST, or, etc.) 3949.7 GL		12. COUNTY OR PARISH 13. STATE ROSWELL, NEW MEXICO	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-11-66: Spudded - ran 11 jts 8 5/8" csg. set at 358', cemented with 350 sac class A cement with 2% cc. Cement circulated. WOC 16 hrs. Tested csg. to 10000'. Tested OK.

12-22-66: Ran 103 jts 4 1/2" csg. set at 3256 - cemented with 250 sac Inco cement. Cement circulated. WOC 24 hrs. Ran temp. survey - top of cement 2150. Tested csg. to 40000'. Tested OK.

1-4-67: Plugged and abandoned as follows: Set 20 sac cement plug 2950-3200
20 sac cement plug 2150-2250
50 sac cement plug 650-750

1-5-67: Turned well over to Federal Bureau of Land Management to test fresh water sands.

RECEIVED
JUN 16 1967
U.S. GEOLOGICAL SURVEY
ARTES, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED Norman Esten TITLE Production Clerk DATE 1-9-67

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

*See Instructions on Reverse Side

JUN 22 1967
J. W. SUTHERLAND

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depth (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-088428

647-831