

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 24 1978

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Borica
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Chaves

O. G. C.
SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-
2. Name of Operator Hanagan Petroleum Corporation
3. Address of Operator P.O. Box 1737, Roswell, New Mexico 88201
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>7S</u> RANGE <u>27E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3955 GR 3966 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/13/78 - Reaming 12¼" hole to 15½" w/cable tools (Tidwell contractor)

7/25/78 - TD 328' - Ran 9 jts. 12 3/4" 34.60# St&c casing (361') in 15½" hole, set @ 328' cmt. (Denton) w/200 sx. Class "C" cement, plug down 3:00 P.M., cement circ.

8/10/78 - Rig up Rotary tool (Moranco), Press. up 600# for 30" no press drop, reamed out to an 11" hole down to 1485', ran 36 jts. 8 5/8" 24# & 32# St&c (1498') set @ 1485', cemented w/350 sx., Class "C" 2% CaCl., plug down 10:30 PM (8/11/78). WOC 18 hrs., (8/12/78), press. up 2000# for 30", no press. drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M.L. Southerland TITLE Agent DATE 8/22/78

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 25 1978

CONDITIONS OF APPROVAL, IF ANY: