

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SEEK IN REPLICATION (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-100891-A

6. IF LEASE, ALLOTTEE OR TRIBE NAME

NON

7. LEASE AGREEMENT NAME

NON

8. NAME OF LEASEE NAME

S. J. Weaver Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SECTION, R., T., OR BLK. AND TOWNSHIP OR AREA

Sec. 35, T-26-S, R-1-E

12. COUNTY OR PARISH

Doña Ana

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL [X] GAS WELL [] OTHER []
2. NAME OF OPERATOR TEXACO Inc.
3. ADDRESS OF OPERATOR P. O. Box 728 - Faber, New Mexico
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
14. PERMIT No. Regular
15. ELEVATIONS (State well depth, RT, CR, etc.) 2435 (D. F.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Total Depth - 5620' - - - 9 5/8" O. P. Casing Cemented at 2435'

We propose to plug and abandon subject well as follows:

- 1. Spot plug No. 1 from 5150' to 5250', (20 Sx. Cement)
2. Spot plug No. 2 from 4300' to 4400', (20 Sx. Cement)
3. Spot plug No. 3 from 2700' to 2800', (20 Sx. Cement)
4. Spot plug No. 4 at (Cast Iron Bridge Plug at 2477') (35 Sx. Cement)
5. Spot plug No. 5 from 2377' to 2477', (20 Sx. Cement)
6. Spot plug No. 6 (Surface plug in 9 5/8" casing) (20 Sx. Cement)
7. Install 4" marker extending 4' above ground level, clean location for inspection as per USGS regulations & MMSGS regulations. Plug and abandon complete 5:00 A. M. January 6, 1966.

RECEIVED
JAN 10 1966
U.S. GEOLOGICAL SURVEY
MEXICO, NEW MEX.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Assistant District Superintendent

DATE

January 6, 1966

(This space for Federal or State office use)

APPROVED BY

[Signature]

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: