

N. M. O. C. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		2. NAME OF OPERATOR TEXACO Inc. ✓		3. ADDRESS OF OPERATOR P.O. Box 728 - Hobbs, New Mexico		4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface: Well located 660' from the South line, and 660' from the West line of Section 35, T-26-S, R-1-E, Dona Ana County, N.M.		5. LEASE DESIGNATION AND SERIAL NO. N-0107891-A		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE		7. UNIT AGREEMENT NAME NONE		8. FARM OR LEASE NAME S. E. Weaver Federal		9. WELL NO. 1		10. FIELD AND POOL, OR WILDCAT Wildcat		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35, T-26-S, R-1-E		12. COUNTY OR PARISH Dona Ana		13. STATE N.M.	
14. PERMIT NO. Regular		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4171' (D. F.)		16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data																					

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Total Depth - 6620' - - - 9-5/8" O.D. Casing Cemented at 2435'
We have plugged and abandoned subject well as follows:

1. Spot plug No. 1 from 5150' to 5250', (20 Sx. Cement)
2. Spot plug No. 2 from 4300' to 4400', (20 Sx. Cement)
3. Spot plug No. 3 from 2700' to 2800', (20 Sx. Cement)
4. Spot plug No. 4 at (Cast Iron Bridge Plug at 2477') (35 Sx. Cement)
5. Spot plug No. 5 from 2377' to 2477', (20 Sx. Cement)
6. Spot plug No. 6 (Surface plug in 9-5/8" Casing) (20 Sx. Cement)
7. Install 4" marker extending 4' above ground level, clean location for inspection as per USGS regulations & NMOC regulations. Plug and abandon complete 5:00 A.M. January 6, 1966. (Verbal permission to plug and abandon subject well received from Mr. J. A. Knauf, District Engineer, January 4, 1966.)

RECEIVED
JAN 10 1966
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Assistant District

DATE January 7, 1966

(This space for Federal or State office use)

SUPERINTENDENT

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: