

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole	7. Unit Agreement Name
2. Name of Operator H. N. Sweeney	8. Farm or Lease Name Rinetta
3. Address of Operator P. O. Box 1582 - Roswell, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER P , 660 FEET FROM THE South LINE AND 660 FEET FROM East 14 LINE, SECTION 8 S TOWNSHIP 38 E RANGE 37 R NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4042 GR	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Perforated 5 1/2 casing 2644-48 and 2652-56 with one shot per foot. Treated with 3000 gallons of 28% acid. Break-down pressure 4000#. Treated at 2900# at 5-1/2 BPM. Swabbed load, acid residue, and formation water with trace of oil.

Set bridging plug at 2650 and swabbed each set of perforations separately. Small show of oil from each.

In accordance with verbal approval from District Supervisor, pumped 25 sack plug on bottom. 2695 2500, shot off 5-1/2" casing at 1795, pulled casing, and set 35 sack plug at base of 8-5/8 casing 1060-955. Shot off 8-5/8" at 368 and pulled. Filled cellar and top of hole with 10 sacks of cement and installed regulation marker. Pumped mud between cement plugs. 4-17-67

RECEIVED

APR 18 1967

ARTERIAL SERVICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. N. Sweeney TITLE Operator DATE April 17, 1967

APPROVED BY R. L. Plam TITLE OIL AND GAS COMMISSIONER DATE MAY 3 1968

CONDITIONS OF APPROVAL, IF ANY: