

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 7
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 351

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chisum Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Chisum S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24-115-27E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ dry hole

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, INC.

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 83201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FNL & 2310' FNL Section 24-115-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3747' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐

SUBSEQUENT REPORT OF:

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

After setting 5 1/2" casing at 2460', completion was attempted by perforating one hole per foot at selected intervals from 2014' to 2444' and acidizing. Perforations at 2414' to 2444' produced salt water and a permanent bridge plug with 1 sack cement was set at 2250'. The perforations from 2085' to 2217' produced salt water and a permanent bridge plug with 1 sack cement was set at 2075'. The perforations at 2014' to 2047' produced oil after acid treatment. Sand/oil fraced with 17,000 gallons oil and 17,000# sand but did not get commercial production. Pursuant to telephone conversation with Mr. Sutherland on August 24, 1962, we plan to plug and abandon by spotting cement through tubing from 2075' to 2000' over perforations presently open and a 10' cement plug and marker at surface.

RECEIVED

AUG 21 1967

AUG 21 1967

RECEIVED
AUG 25 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Grant M. SmithTITLE GeologistDATE Aug. 24, 1967

(This space for Federal or State office use)

APPROVED BY APPROVED

TITLE

AUG 28 1967
J. W. SUTHERLAND
DISTRICT ENGINEER

*See Instructions on Reverse Side

AUG 28 1967

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable local, area, or regional procedures and practices, either as shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-695226

507-881

APPROVED