

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR CATE*
(Other instruction on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 1717

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR FRANKLIN, ASTON & FAIR, INC.		8. FARM OR LEASE NAME Cruz Federal	
3. ADDRESS OF OPERATOR P. O. Box 1090, Roswell, New Mexico 88201		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNSWL's Sec. 31-14S-25E		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31-14S-25E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3640' GR		12. COUNTY OR PARISH Chaves	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Commenced drilling operations September 26 and drilled 12 1/4' hole to 1210'. Ran 9 5/8' 32# J-55 new casing which stuck at 1120'. Cemented with 650 sacks cement which did not circulate. Ran temperature survey and found cement outside casing at 925'. Ran macaroni string to 650' and pumped 50 sacks cement. Pulled up and found top of cement at 450'. Pumped additional 50 sacks cement and found top of casing at 420'. Continued to stage cement until top of cement at 135'. With permission of U.S.G.S. Ready-Mix was run around top of casing. Mr. Charles I. Saunderson, U.S.G.S. representative, was present and approved cementing procedure.

RECEIVED
OCT-7 1968
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE

18. I hereby certify that the foregoing is true and correct

SIGNED Grant M. Smith TITLE Geologist DATE 10-7-68

(This space for Federal or State office use)

APPROVED BY R. L. DEAN TITLE Geologist DATE 10-7-68

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
R. L. DEAN
ACTING DISTRICT SUPERVISOR

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.