

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
K-6623

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Charles B. Read	8. Farm or Lease Name Hondo-State
3. Address of Operator P. O. Box 2126 Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>14S</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat Buffalo Valley-Penn Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3470.5 GL	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-5-68: Ran 9 jts, 12 3/4", 48#, FWPS csg, 333.38' set @ 318' RKB. Cmt w/300 sx 50/50 Incor Poz, 4% gel, 1/4# Flo Seal & 8# salt per sx. Followed w/100 sx 50/50 Poz, 2% gel, 1/4# Flo Seal & 8# salt per sx. Plug down @ 3 PM. Cmt circ. WOC 18 hrs. Tested to 600 PSI for 30 min - Test OK.

12-7-68: Ran 44 jts, 8 5/8", 32#, J-55 csg, 1569.39' set @ 1550' RKB. Cmt w/200 sx Incor, w/2% CaCl. Plug down @ 9:30 AM. 12-7-68. WOC 18 hrs. Press test to 1500 PSI - Test OK.

Commenced drilling operations on 12-4-68.

RECEIVED

DEC 11 1968

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles B. Read TITLE Agent DATE 12-9-68

APPROVED BY W. A. Grissett TITLE OIL AND GAS INSPECTOR DATE DEC 12 1968
CONDITIONS OF APPROVAL, IF ANY: