

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

T. Anhy _____	T. Canyon <u>7288</u>
T. Salt _____	T. Strawn <u>7757</u>
B. Salt _____	T. Atoka <u>8072</u>
T. Yates _____	T. Miss <u>8425</u>
T. 7 Rivers _____	T. Devonian _____
T. Queen <u>847</u>	T. Silurian _____
T. Grayburg <u>1210</u>	T. Montoya _____
T. San Andres <u>1508</u>	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinebry _____	T. Gr. Wash _____
T. Tubb <u>4258</u>	T. Granite _____
T. Drinkard _____	T. Delaware Sand _____
T. Abo <u>5030</u>	T. Bone Springs _____
T. Wolfcamp _____	T. _____
T. Penn. _____	T. _____
T. Cisco (Bough C) <u>6897</u>	T. _____

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Qtzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)						
From	To	Thickness in Feet	Formation	From	To	Thickness in Feet
0	850		Anhy & Dolo			
850	1210		Sand, Shale & Anhy	DST#1	8161' - 8258'	1 hr
1210	1500		Dolo, Shale & Anhy		No gas to surface, rec 30' mud	
1500	2850		Dolo & Anhy		IFP 9#, FFP 9#, 60 SI 69#	
2850	4250		Anhy, Shale & Dolo	DST#2	8258' - 8358'	Pkr failed
4250	4400		Sand			
4400	5020		Dolo, Shale & Anhy	DST#3	8167' - 8358'	1 hr
5020	5430		Red Shale & Anhy		GTS 3"	
5430	6150		Dolo & Anhy		Rec 468' GCM	
6150	6900		Lime & Shale		IFP 92#	
6900	7300		Shale & Lime		FFP 92#	
7300	7750		Lime & Shale		2 hr SI 3034#	
7750	8070		Lime, Sand & Shale			
8070	8420		Shale, Sand & Lime			
8420	8504		Lime & Shale			