

NO. OF COPIES RECEIVED	3
DISTRIBUTION	1
SANTA FE	1 ✓
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
FEB 9 1977
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
K-6623

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- <u>RE-ENTRY</u>	7. Unit Agreement Name
2. Name of Operator <u>Mountain States Petroleum Corp.</u>	8. Farm or Lease Name <u>HONDO - STATE</u>
3. Address of Operator <u>P.O. Box 1936 Roswell, NM 88201</u>	9. Well No. <u>1</u>
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>14S</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat <u>Buffalo Valley Penn</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3470.5 GL</u>	12. County <u>Chaves</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER <u>Treating & Perfs</u> ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1403.

Reperforated 1-11-77

1-14 Cleaned off old 8-5/8" csg at 844.5' milled off 15". Ran 29 jts 24# J-55 8-5/8" csg with Bowen Casing Bowl. Tied-in. Pressured to 500 psi for 30 min. Pressure held.

1-23 Reached OTD 8504. Drilled 8504-8514. New TD 8514

1-24 Ran 243 jts 4-1/2" csg N-80 and J-55, 10.5 & 11.6# set at 8406 RKB. Ran flapper valve float with 6 centralizers. Cemented w/ 350 sxs class C + 3/4% D-60 and 2% D-46. Displaced with 2% KCl wtr. Pressured 650 psi 2 hours. Temp survey top cement 7100.

1-26 Perf 2 SPF (.320) 8336-45, 8262-73, 8155-64 (58 shots).

2-1 Pkr 8106. Acid 4000 gals 7-1/2% HCl all perfs.

2-2 Testing, no gauges.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. Chavienor TITLE Geologist DATE 2-8-77

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE FEB 10 1977

CONDITIONS OF APPROVAL, IF ANY: