

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JUL 15 1971

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator MERCURY PRODUCTION COMPANY		5. State Oil & Gas Lease No. K-5739
3. Address of Operator 809 Ft. Worth Nat'l Bank Bldg., Ft. Worth, Texas 76102		7. Unit Agreement Name
4. Location of Well UNIT LETTER E , 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 27 TOWNSHIP 10S RANGE 26E NMPM.		8. Farm or Lease Name Mercury State
15. Elevation (Show whether DF, RT, GR, etc.)		9. Well No. 1
12. County Chaves		10. Field and Pool, or Wildcat Wildcat

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <u>Re-entry and recompletion</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out cement plugs to a new T.D. of 5867' on May 9, 1971. Ran 4 1/2" 10.5#, J-55 casing to 5866' and cemented with 225 sacks of Dowell expanding cement. P.B.T.D. 5858'. Perforated 5784-5794', 5828-5834', 5837-5846' w/2 jet shots/ft. Acidized perms. w/500 gal. MCA. Swabbed mud and gas, T.S.T.M. Fracture treated w/8200# sand in My-T-Frac gel. Treated @ 6 BPM w/3600#. Instant shut-down 1700#, 15 min. shut-down 500#. Swabbed salt water @ rate of 20 BPH with fluid level standing 1000' from surface. No shows of gas. Shut well in - waiting on orders.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank Darden TITLE President DATE 7-13-71

APPROVED BY W.A. Gressett TITLE OIL AND GAS INSPECTOR DATE JUL 16 1971

CONDITIONS OF APPROVAL, IF ANY: