

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

AUG 24 1970

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-841
7. Unit Agreement Name -----
8. Farm or Lease Name Sun State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator McGrath & Smith, Inc.
3. Address of Operator 418 Building of the Southwest, Midland, Texas 79701
4. Location of Well UNIT LETTER 0, 1980 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 27 TOWNSHIP 14-S RANGE 28-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) GL 3595 KB 3606

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input checked="" type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input type="checkbox"/>		<input type="checkbox"/>
OTHER	<input type="checkbox"/>		<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded 12:30 noon, 8-12-70. Drld. 12 1/4" hole to 365'. Cmt. 8 5/8-20# csg. at 365' with 200 sx. Circ. 15 sx. Plug down 4:30 pm, 8-12-70. WOC 18 hrs. Tested 8 5/8" to 350 psi - OK. Drld. 7 7/8 hole to TD 1925'. Cored 1258-1286. NS Reached Td at 5:00 pm, 8-15-70. Ran GR-Acoustic, LL, MLL logs.

Propose to P & A as follows: Spot cmt. plugs as follows: 25 sx. at TD, 25 sx. at top Queen, 25 sx. at base salt, 25 sx. at top salt, 25 sx. across base of 8 5/8, 10 sx. in top of 8 5/8. Install DHM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>W. A. Gressett</u>	TITLE <u>Sup't.</u>	DATE <u>8-17-70</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>Sup't.</u>	DATE <u>8-17-70</u>
CONDITIONS OF APPROVAL, IF ANY:		