

NO. OF COPIES RECEIVED	1
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 29 1970

E. B. L.
ARTICIAL OFFICE

30-005-60140

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease
STATE ☒ FEE ☐
5. State Oil & Gas Lease No.
K-5432

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
1. Type of Well OIL WELL ☒ GAS WELL ☐ OTHER ☐ DRILL ☒ DEEPEN ☐ PLUG BACK ☐ SINGLE ZONE ☐ MULTIPLE ZONE ☐		8. Farm or Lease Name Gratton State	
2. Name of Operator Eugene E. Nearburg		9. Well No. 1	
3. Address of Operator 4219 Sigma Rd., Dallas, Texas		10. Field and Pool, or Wildcat Wildcat	
4. Location of Well UNIT LETTER P LOCATED 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE OF SEC. 18 TWP. 4S RGE. 27E NMPM		12. County Chaves	
19. Proposed Depth 6750'		19A. Formation Devonian	
20. Rotary or C.T. Rotary		21. Elevations (Show whether DP, RT, etc.) 3879.2	
21A. Kind & Status Plug. Bond State Wide		21B. Drilling Contractor WEK Drilling Co., Inc.	
22. Approx. Date Work will start Oct. 1, 1970			

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11"	8 5/8"	24# J-55	1400	Circulate	Surface
7 7/8"	4 1/2"	11.6 - 9.5	6750	250	5650

Drill 11" hole to 1400'. Run 1400' 8 5/8", J-55-24# casing and circulate cement to surface.

Drill 7 7/8" hole to T.D. and run oil string if production is indicated.

Cement W/250 sx 50/50 Incor Posmix, 2% Gel and 6# Salt/sx.
BOP to be installed after setting 8 5/8" casing.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,
EXPIRES 12-29-70

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Eugene E. Nearburg Title Production Supt. Date 9/29/70

(This space for State Use)

APPROVED BY W. A. Grossett TITLE OIL AND GAS INSPECTOR DATE SEP 29 1970

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 8 5/8" casing