

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other instruc. * on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 038096

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

NA

8. FARM OR LEASE NAME

Shenandoah Federal "J"

9. WELL NO.

1

10. FIELD AND POOL, OR WIELD CAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

5-T7S-R27E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL
WELL☐GAS
WELL☒

OTHER

Dry Hole

2. NAME OF OPERATOR

Shenandoah Oil Corporation

3. ADDRESS OF OPERATOR

1500 Commerce Building - Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

2130' FNL & 660' FWL of Section 5-T7S-R27E

14. PERMIT NO.

-

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3904' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Pursuant to verbal approval this well was plugged and abandoned as a dry hole after drilling to a
total depth of 1822'. Plugging operations were performed as follows:

Spotted 50 sx. Class "H" cmt. plug from 1722-1622'
Spotted 40 sx. Class "H" cmt. plug from 130-50'
Spotted 10 sx. Class "H" cmt plug in top of 13 3/8" surface casing.
Steel plate was welded on top and an identification marker installed.
Abandonment was completed 1:00 p.m. 11-28-70. FINAL REPORT

Logs are being transmitted under separate cover.

RECEIVED

MAY 7 1971

O. G. C.
ARTESIA, OFFICE

RECEIVED

DEC-2 1970

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Nabbefeld

TITLE

Manager, Drilling and
Primary Operations

DATE

November 30, 1970

(This space for Federal or State office use)

APPROVED BY
COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

MAY - 6 1971

R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of packing any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-485229

APPROVED
JAN 10 - 1984
J. J. BERNARD
DIRECTOR, BUREAU OF LAND MANAGEMENT