

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
OCT 8 1971
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator WILLIAM G. MCCOY ✓	8. Farm or Lease Name Edelweiss
3. Address of Operator P.O. BOX 1352 ROSWELL, NM 88201	9. Well No. 1
4. Location of Well UNIT LETTER A , 990 FEET FROM THE North LINE AND 990 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 5-S RANGE 26-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4044.2 G.L.	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-27-71 Well spudded 7:00 P.M. Spudded with verbal permission of

Mr.W.A.Gressett.

9-30-71 T.D.1356 feet. Ran 42 joints of 8-5/8" - 24#-K-55 casing. Set at 1356 feet. Cemented with 550 sx.Haliburton Lite with 5# Gilsonite per sx. + 2% CaCl. and 150 sx. Class "C" with 2% CaCl.Total 700 sx. Circulated out 10 sx. Plug down 7:00 P.M.

10-1-71 W.O.C. 18 hrs. Tested casing with 1000# for 30 minutes. No leaks, drilled out.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED William G. McCoy TITLE Operator DATE 10-7-71

APPROVED BY W.A. Gressett TITLE OIL AND GAS INSPECTOR DATE OCT 8 1971

CONDITIONS OF APPROVAL, IF ANY:

