

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-012255A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "T"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., E., M., OR BLE. AND
SURVEY OR AREA

Sec. 23 T 11S R 26E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	14. PERMIT NO.
2. NAME OF OPERATOR Shenandoah Oil Corporation	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3632 GR
3. ADDRESS OF OPERATOR 702 Gihls Tower West, Midland, Texas 79701	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL 1980' FEL Sec 23 T 11S R 26E	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17½" hole at 11 A. M. 9/27/72. Drilled to 407' RKB. Ran 13 joints 13 3/8" 48# surface casing landed at 407' RKB. Cemented with 400 sx. Class "C" cement with 2% calcium chlorides. Cement did not circulate. Plug down 5:30 A. M. 9/28/72. Re-cemented outside casing with 50 sx. Encor Neat cement with 2% calcium chlorides. Plug down 10:30 A.M. 9/28/72. W. O. C. 24 hrs. Pressure test casing & BOP's to 1000 psi for 30 min. pressure held. Drilled 11" hole to 1265' RKB. Ran 40 joints 8 5/8" intermediate casing landed at 1265' RKB. Cemented with 350 sx Lite weight cement with 8# Gilsonite per sx. 1/4# flocele per sx and 2% calcium chlorides. Plug down at 7:45 P.M. 10/1/72. Cement did not circulate. W. O. C. 18 hrs.

18. I hereby certify that the foregoing is true and correct

SIGNED

THOMAS E. FENNO

TITLE

Dist. Production Supt.

DATE

10-25-72

(This space for Federal or State office use)

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

RECEIVED
JAN 15 1964
U.S. DEPT. OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
DENVER, COLORADO