

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG-4681	
7. Unit Agreement Name	
8. Farm or Lease Name	
Citgo "A" State	
9. Well No.	
8	
10. Field and Pool, or Wildcat Assoc.	
Twin Lakes-San Andres	
12. County	
Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>
Name of Operator		
STEVENS OIL COMPANY		
Address of Operator		
P. O. Box 2203 - Roswell, New Mexico 88201		
Location of Well		
UNIT LETTER	H	2310 FEET FROM THE North LINE AND 990 FEET FROM
THE East	LINE, SECTION 36	TOWNSHIP 8-S RANGE 28-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3857.6 Gr., 3862.6 K.B.

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER <input type="checkbox"/>
	ALTERING CASING <input type="checkbox"/>
	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5-31-79 Spud 11:00 a.m., drilled 80' and ran 80' 8-5/8" 28# surface casing; circulated cement w/2 hards ready-mix. WOC/
- 6-09-79 Spudded 5:00 p.m. w/rotary.
- 6-14-79 Ran 2730' 4-1/2" 9.5# casing to T.D. and cemented with 150 sacks Class "C" and 75 sacks self-stress cement.
- 6-16-79 Perf. 2623.5, 24, 26, 26.5, 27, 29.5, 30, 41, 41.5, 42, 46, 46.5, 48, 48.5, 49, 49.5, 53.5, 54, 54.5, 57.5, 58, 59.5, 60, 60.5, 62.5, 63.5, 64, 64.5
- 6-19-79 Acidized perms. with 7000 gallons 28%, swabbing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	<i>Donald G. Smith</i>	TITLE	Owner	DATE	6-21-79
APPROVED BY	<i>W. A. Gessert</i>	TITLE	SUPERVISOR, DISTRICT 41	DATE	JUN 22 1979
CONDITIONS OF APPROVAL, IF ANY:					