

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

JUN 5 1980

Form C-103
Revised 10-1-78

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 4. Location of Well UNIT LETTER <u>E</u> 1980 FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>7S</u> RANGE <u>24E</u> NMPM.	7. Unit Agreement Name 8. Farm or Lease Name West Dixon NX State 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat 15. Elevation (Show whether DF, RT, GR, etc.) 3697' GR 12. County Chaves
--	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
COMMENCE DRILLING OPNS.
CASING TEST AND CEMENT JOBS
OTHER

ALTERING CASINGS
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in rat hole digger and drilled a 20" hole to 40'. Set 40' of conductor pipe w/3yards of Ready-mix. (5-23-80). Moved out rat hole digger.
 TD 40' - Moved in rotary tools and started reaming a 17½" at 1:00 PM 5-24-80.
 TD 412'- Ran 8 joints of 13-3/8" 48# K-55 (292') of casing set at 285'. 1-Texas Pattern guide shoe at 285'. 1-Flapper insert float at 250'. Could not get casing to TD. Cemented w/400 sacks of Class C 4% CaCl. PD 7:45 PM 5-25-80. Slurry weight 14.8, 1.32 cu ft/sx. Compressive Strength at 70 degrees 1023 ps. in 12 hours. Cement did not circulate. WOC and filled hole w/8 yards of Ready Mix. WOC 12 hours, backed off and reduced hole to 12¼", drilled plug and tested to 600# OK and resumed drilling.
 TD 1553'- Ran 39 jts of 8-5/8" 24# J-55 (1553') of casing set at 1553'. 1-guide shoe at 1553'. Cmtd w/550 sx Howco Lite 5#/sx Gilsonite, 1/4#/sx Cello-flakes, 2% CaCl, followed w/150 sx Class C 2% CaCl. PD 11:45 PM 5-28-80. Cmt did not circ. WOC ran Temp. Srvy, found top of cement at 320', spotted 150 sx Class C 4% CaCl. PD 7:30 AM 5-29-80. Circ. 10 sx to surface. Cmt fell & filled to surface w/8 yds RM. WOC 18 hrs, NU, tested to 1500# OK, reduced hole to 7-7, drilled plug, tstd to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomblin TITLE Geol. Secty DATE 6-4-80

APPROVED BY W.A. Gussett TITLE SUPERVISOR, DISTRICT II DATE JUN 5 1980

CONDITIONS OF APPROVAL, IF ANY: