

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructions
reverse side)DATE
on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-14755

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Powers OL Federal Com.

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat Und. Also

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit I, Sec. 14-6S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3622.8' GR

12. COUNTY OR PARISH

Chaves

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 17-1/2" hole at 4:00 PM 12-1-80.

TD 465' Ran 11 joints of 13-3/8" 54.50# of casing set at 465'. No shoe. Flapper float at 420'. Cemented w/450 sacks Class C 4% CaCl. PD 8:30 AM 12-2-80. Cement circulated 85 sacks. WOC 12 hours. Backed off and reduced hole to 7-7/8". Drilled plug and tested to 600 psi, OK.

TD 1360' Ran 33 joints of 8-5/8" 24# J-55 ST&C casing set at 1360'. 1-Texas pattern guide shoe at 1360'. Insert float at 1314'. Cemented w/570 sacks 65-35 Poz, 4% D-20, 8#/sack D-42, 1/4# D-29 and 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 6:00 PM 12-9-80. Cement circulated 5 sacks to pit. Cement fell back. WOC 6 hours. Ran Temperature Survey and found top of cement at 250'. Ran 1". Tagged cement at 250'. Spotted 50 sacks Class C 4% CaCl. PD 3:00 AM 12-9-80. Circulated 25 sacks. WOC 18 hours. Nippled up and tested to 1500 psi, OK. Reduced hole to 7-7/8" Drilled plug and tested to 600 psi, OK.

RECEIVED
DEC 11 1980U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

Dec. 10, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

DEC 11 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
JAN 11 1964
U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT