

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Fred Pool Drilling Co</u>		Lease <u>Honda River Farm</u>		Well # <u>1</u>	
Location of Well	Unit <u>1480 N 1920 W F</u>	Section <u>4</u>	Township <u>11</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor	<u>Fred Pool</u>		Type of Equipment <u>Rotary</u>		

1 * witness

2 * witness if possible

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per	New or Used	Depth	Sacks Cement
24"	20"	60# Foot		40'	Red. mix
17 1/2"	13 3/8"	54#		700'	450 SX - Circ
12 1/4"	8 5/8"	24#		1200'	650 SX - Circ
7 7/8"	4 1/2"	10.5#		6000'	800 SX

Casing Data:

Surface joints of 13 3/8 inch 54 # Grade J-55

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 13 3/8 Sacks cement required _____

Type of Shoe used guide Float collar used No Btm 3 jts welded Yes

TD of hole 679' Set 679' Feet of 13 3/8 Inch 54 # Grade K-55

New used csg. @ 679' with 220 sacks neat cement around shoe

+ 500 sack 6 3/8 pipe additives (470, 5# salt, 1/4# celofake, 39#)

Plug down @ 4:00 (AM) (PM) Date 12/23/80

Cement circulated No No. of Sacks 0

Cemented by Dowell Witnessed by Mike Stubblefield

Temp. Survey ran @ 12:00 (AM) (PM) Date 12/23/80 top cement @ 15'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Operator ready-mixed well to surface

Full turn to TD

last day break @ 672'

No centralizer