

F. 100-101
M. 100-101UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THIS CASE

WELL NO. 42 11474

NM-28306

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Use this form for proposals to drill or to plug back to a different reservoir.
(Use APPLICATION FOR PERMIT for each proposal.)

| | | | |
|--|--|---|--|
| 1. WELL TYPE OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | | 7. UNIT AGREEMENT NAME | |
| 2. NAME OF OPERATOR McClellan Oil Corporation / | | 8. FARM OR LEASE NAME Coyote Draw Federal | |
| 3. ADDRESS OF OPERATOR Post Office Drawer 730, Roswell, New Mexico 88201 | | 9. WELL NO. 1 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 660' FWL | | 10. FIELD AND POOL, OR WILDCAT Wildcat | |
| 11. PERMIT NO. | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 6-T8S-R25E | |
| 15. ELEVATIONS (Show whether LT, RT, GR, etc.) 3776 G.L. | | 12. COUNTY OR PARISH Chaves | |
| | | 13. STATE NM | |

RECEIVED

APR 10 1981

O. C. D.

ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Casing report

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3/25/81: Drilled to 1710' with 12 1/4" bit. Ran 1713' of 8-5/8", 23 lb/ft, J-55 casing. Cemented with 1000 gals. Flo-Chek, 100 sacks "Thixset", 575 sacks Halliburton Light with 5 lb/sx Gilsonite and 1/2 lb/sx Flocele, 200 sacks Class "C" with 2% CaCl₂. Did not circulate cement. Waited 6 hours. Ran temperature survey. TOC at 500'.

3/26/81: Ran 1" tubing between 8-5/8" and 13-3/8" and cemented with 300 gallons of Flo-Chek and 200 sacks of Class "C" Thixset cement. Tagged cement after two hours at 156'. Waited on cement 18 hours and tested casing to 500 psi for 30 min.

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Engineer

DATE 3/27/81

APPROVED BY PETER W. CHESTER

APR 8 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side