

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 22615

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

MAR 09 1981

8. FARM OR LEASE NAME

CAMACK FEDERAL O. C. D.

9. WELL NO.

ARTESIA OFFICE

1

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SEC 9, T5S, R24E

12. COUNTY OR PARISH

13. STATE

CHAVES

NEW MEXICO

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR

1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4015' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SPUD & 13 3/8" CSG/CEMENT

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 17 1/2" hole on 2-26-81. Hit fresh water at 290' - est 20 BWPH and at 650' - est 100 BWPH. Drilled to 800'. Ran 19 jts, 48#, H-40 casing set at 797'. Cemented with 350 sx Lt + 4% CaCl, 100 sx Thixset + 4% CaCl, 350 sx Lt + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. Cement did not circulate. Set plug #1 with 120 sx Thixset + 4% CaCl. Circulated 10 sx to surface. Reduced hole to 11" and drilled ahead on 3-2-81. Hit fresh water at 860' - estimated at 100 BPH.

RECEIVED  
MAR 06 1981

XC: USGS (6), TLS, CEN RCDS, ACCTG, HOBBS, MEC, LAND, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

R. F. Matson

TITLE

REGULATORY COORDINATOR

DATE MARCH 4, 1981

(This space for Federal or State office use)

PETER W. CHESTER

APPROVED BY

CONDITIONS OF APPROVAL

MAR 6 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side