Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ sur TOC 13 3/8" casing @ su XC: BLM-R (0+2), NMOCD-A, WF, 8. I hereby certify that the foregoing is true and co SIGNED	Sg set @ 910 aise cement & 00' (by temp s face urface CR, Acctg, E	<pre>') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey) xpl., Land, Reg, Pa egulatory Agent</pre>	" csg annu	DEC 2 0 DEC 2 0 12-11- CHESTER 0 1985	-85		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ sur TOC 13 3/8" casing @ su XC: BLM-R (0+2), NMOCD-A, WF, 8. I hereby certify that the foregoing is true and co SIGNED	Sg set @ 910 aise cement f 0' (by temp s face urface CR, Acctg, E <u>prrect</u>	<pre>') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey) xpl., Land, Reg, Pa</pre>	" csg annu " Hog Thers DAT	DEC 2 0	MEXICO		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ sur TOC 13 3/8" casing @ sur 	sg set @ 910 aise cement f 00' (by temp s face urface CR, Acctg, E:	<pre>') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey) xpl., Land, Reg, Pa</pre>	" csg annu " Hog Thers DAT	DEC 2 0	MEXICO		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ sur TOC 13 3/8" casing @ sur 	sg set @ 910 aise cement f 00' (by temp s face urface CR, Acctg, E:	<pre>') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey) xpl., Land, Reg, Pa</pre>	" csg annu " " " " " " " " " " " " " " " " " "	DEC 2 0	MEXICO		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ sur	Sg set @ 910 aise cement & 00' (by temp s face urface CR, Acctg, E	<pre>') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey) xpl., Land, Reg, Pa</pre>	" csg annu	DEC 2 0	MEXICO		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ su	sg set @ 910 aise cement # 00' (by temp s face urface	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey)	" csg annu	DEC 2 0	,000		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur TOC 13 3/8" casing @ su	sg set @ 910 aise cement # 00' (by temp s face urface	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2 survey)	" csg annu	DEC 2 0	,000		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur	sg set @ 910 aise cement # 00' (by temp s face	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2	" csg annu	DEC 2 0	,000		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur	sg set @ 910 aise cement # 00' (by temp s face	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2	" csg annu	DEC 2 0	,000		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur	sg set @ 910 aise cement # 00' (by temp s face	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2	" csg annu	UOF LAND			
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur	sg set @ 910 aise cement # 00' (by temp s face	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2	" csg annu	JOF LAND			
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110 TOC 8 5/8" casing @ sur	sg set @ 910 aise cement # 00' (by temp s face	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2	" csg annu	JOF LAND			
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r Install dry hole marker. NOTE: TOC 4 1/2" casing @ 110	aise cement of '() '() '() '() '() '() '() '() '() '()	') from 1990'-1890' ') from 960'-860' to surface in 4 1/2		lus.	and the second		
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r	sg set @ 910 aise cement #	') from 1990'-1890' ') from 960'-860'		lus.			
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface RIH with 1" tubing and r	sg set @ 910 aise cement #	') from 1990'-1890' ') from 960'-860'		lus.			
Set 100' plug (8 5/8" cs Set 100' plug (13 3/8" c Set 50' plug to surface	sg set @ 910	') from 1990'-1890' ') from 960'-860'					
Set 100' plug (8 5/8" cs		') from 1990'-1890'	,				
	X SEL 1940						
		J PELLO JILA -J240					
Set CIBP @ 3650' plus 35	comont (Ah	n nerfe 371/1-30/61	<b>`</b>				
Propose to P&A well as foll	ows:						
proposed work. If well is directionally drilled, nent to this work.) •	give subsuriace locs	mous and measured and true ve	incar depins for	all markers and	sones perti-		
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Cle	arly state all pertines	Completion or Reconct details, and give pertinent details.	tes, including es	timated date of	starting any		
REPAIR WELL CHANGE PLAN (Other)	s	(Other)	ults of multiple	completion on W	 Vell		
SHOOT OR ACIDIZE ABANDON*	X	SHOOTING OR ACIDIZING		ABANDONMENT <sup>*</sup>			
FRACTURE TREAT MULTIPLE CO	MPLETE	WATER SHUT-OFF Fracture treatment		REPAIRING WELL ALTERING CASING			
TEST WATER SHUT-OFF PULL OR ALTI							
NOTICE OF INTENTION TO :			SEQUENT REPORT	or :			
6. Check Appropriate	Box To Indicate 1	Nature of Notice, Report, c	or Other Data				
	3995	' GR	Chave	es	NM		
4. PERMIT NO. 15. ELEVAT	cions (Show whether Di	F, RT, GR, etc.)	12. COUNT	OR PARISE 13.	STATE		
	_		Sec.	18, T6S, R	25E		
ANIMA COUCTEL ANIMA			11. SEC., T SUL	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA			
See also space 17 below.) At surface 660' FNL & 660' FEL		ARTESIA, OFFICE		Slope Abo			
P.O. Box 2009, Amarillo, T L. LOCATION OF WELL (Report location clearly and in		State of the D	10. FIELD	2 AND POOL, OR WII	LDCAT		
B. ADDRESS OF OPERATOR	awag 70190	DEC 31 1900	9. WBLL M	_			
Mesa Petroleum Co.	Τ	10Gh		FORD FEDER	AL		
OIL GAS X OTHER		RECEIVED BY	8. FARM OF	LEASE NAME			
Gil GAS 🔽			7. UNIT AG	BREMENT NAME			
(Do not use this form for proposals to drill Use "APPLICATION FOR	or to deepen or plug PERMIT—" for such p	back to a different reservoir. proposals.)					
	ID REPORTS	ON WELLS	U. IF INDIA	IN, ALLOTTEE OR	TEIBE NAMÉ		
SUNDRY NOTICES AN		BUREAU OF LAND MANAGEMENT			NM-20337 6. IF INDIAN, ALLOTTEE OF TRIBE NAME		
BUREAU OF LAN	ND MANAGEMEN		I N	5. LEASE DESIGNATION AND SERIAL NO.			
Cormerly 9–331) DEPARTMEN I OI BUREAU OF LAN SUNDRY NOTICES AN	F THE INTER		5. LEASE D				
November 1983) Formerly 9–331) DEPARTMEN I OI BUREAU OF LAN SUNDRY NOTICES AN	F THE INTER	ORi verne Wie) 88210	re- Expir	et Bureau No. 1 es August 31, ESIGNATION AND	1985		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.