MIDLAND, TX.

SUBSEQUENT REPORT OF:

Form 9-331 Dec. 1973

well

2. NAME OF OPERATOR

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

other

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.

~ cement

ROSWELL, NEW MEXICO

gas

well

MESA PETROLEUM CO., 3. ADDRESS OF OPERATOR 1000 VAUGHN BLDG.

REPORT, OR OTHER DATA

4 1/2"

csq

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON*

(other)

X

AT SURFACE: 1980' FSL & 1650' FEL

AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same

	Budget Bureau No. 42-R1424
5.	LEASE
	_NM 36652
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
7.	UNIT AGREEMENT NAME
	FARM OR LEASE NAME
8.	TARM OR LEASE NAME
	BARN FEDERAL IIII a
9,	WELL NO. JUL 2 9 198
	4
10.	FIELD OR WILDCAT NAME RIFE. C. D.
	UNDESIGNATED ABO ARTESIA OFFICE
11.	FIELD OR WILDCAT NAME RTESIA, OFFICE SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	SEC 13, T8S, R22E
12.	COUNTY OR PARISH 13. STATE
	CHAVES NEW MEXICO
14.	API NO.
15.	ELEVATIONS (SHOW DF, KDB, AND WD)

Report results of multiple completion or zone

3985.5'GR

TORVEY 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

U.S. GER

Drilled 7-7/8" hole to total depth of 3350' on 7-18-81. Ran 81 jts 4 1/2", 10.5#, k55 casing set at 3316'. Cemented with 600 sx HLW + 10# salt + 1/4# Flocele, and tailed in with 300 sx 50-50 pozmix + 2% ge1 + 8# salt + 3/10% CFR-2. PD at 12 noon 7-19-81. Circulated 75 sx. Released rig at midnight 7-19-81. WOCU estimated to arrive 8-1-81.

USGS (3), TLS, CENT RCDS, ACCTD, ROSWELL, MEC, LAND, PARTNERS, FILE

Subsurface Safe	ety Valve: Manu. and Type	Set @ Ft.
18. I hereby ce	rtify that the foregoing is true and correct	
SIGNED R.	E. Marker TITLE REG COORDINAT	TOR DATE 7-22-81
	ACCEPTED FOR RECORDS space for Federal or State office	e use)
APPROVED BY	ROGER A. CHAPMAN TITLE	DATE
	APPROVAL, IF ANY:	
	JUL 2 7 1981	
	U.S. GEOLOGICAL SURVEY Instructions on Reverse Sid	da