Dec. 1973	NM OIL COTT. COMMISSION Drawer DL	Form Approved. Budget Bureau No. 42-R1424
	Artesiaunimed88720ES	5. LEASE NM 23264
	DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDR	DEPORTS ON WELLS	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)		8. FARM OR LEASE NAME
1. oil well	gas 🕅 other	9. WELL NO.
	F OPERATOR ETROLEUM CO. /	10. FIELD OR WILDCAT NAME
3. ADDRES	S OF OPERATOR AUGHN BUILDING/MIDLAND, TEXAS 79701	UNDESIGNATED ABO 11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATIO	IN OF WELL (REPORT LOCATION CLEARLY. See space 17	
below.) AT SURI	FACE: 1980' FSL & 660' FWL	12. COUNTY OR PARISH 13. STATE CHAVES NEW MEXICO
AT TOTA	PROD. INTERVAL: AL DEPTH:	14. API NO.
	APPROPRIATE BOX TO INDICATE NATURE OF NOTICE , OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
	OR APPROVAL TO: SUBSEQUENT REPORT OF	4064.9' GR
TEST WATER		
SHOOT OR REPAIR WEI		1981NOTE: Report results of multiple completian or zor
CHANGE ZO		ICAL SURVE
ABANDON* (other)_SPL	ID & 8 5/8" CSG & CEMENT ROSWELL, N	
	BE PROPOSED OR COMPLETED OPERATIONS (Clearly s ing estimated date of starting any proposed work. If well is	
measur	ed and true vertical depths for all markers and zones pertin	nent to this work.)*
measur		
		4i+ FW at 194' - TSTM.
J <sub>Spudde</sub>	ed well with 12 $1/4$ " hole on 8-2-81.	lit FW at 194' - TSTM. an 34 its 8 5/8", 24#, K-55,
J <sub>Spudde</sub> Lost i casing	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM
Spudde Lost casing sx Th	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set
Spudde Lost casing sx Th 8-6-8	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx.
Spudde Lost casing sx Th 8-6-8 three Bodus	ed well with 12 1/4" hole on 8-2-81. F returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx F ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK.
Spudde Lost casing sx Th 8-6-8 three Reduc Drill	ed well with 12 1/4" hole on 8-2-81. F returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx F ixset + 4% CaCl, tailed in with 200 sx l. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 ho	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours.
Spudde Lost casing sx Th 8-6-8 three Reduce Drill Note:	ed well with 12 1/4" hole on 8-2-81. F returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx F ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 ho Cement job witnessed by B. Jones/USG	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S.
Spudde Lost casing sx Th 8-6-8 three Reduce Drill Note:	ed well with 12 1/4" hole on 8-2-81. F returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx F ixset + 4% CaCl, tailed in with 200 sx l. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 ho	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S.
Spudde Lost casine sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 h Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, estify that the foregoing is true and correct	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM 
Spudde Lost i casine sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface 18. Theref	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 h Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, safety Valve: Manu. and Type by certify that the foregoing is true and correct <b>P. Machine Science</b> , TREGULATORY COO	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM Set @ PRDINATOBATEAUGUST 10, 1981
Spudde Lost casing sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface 18. I heret	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 he Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, safety Valve: Manu. and Type by certify that the foregoing is true and correct REGULATORY COO CCEPTED FOR RECORD (This space for Federal or Stat	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM Set @ PRDINATOBATEAUGUST 10, 1981 
Spudde Lost i casing sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface 18. I heret SIGNED	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 h Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, Safety Valve: Manu. and Type Dy certify that the foregoing is true and correct CEPTED FOR RECORD OGER A. CHAPMAN BY S OF APPROVAL, IF ANY:	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM Set @ PRDINATOBATEAUGUST 10, 1981
Spudde Lost i casing sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface 18. I heret SIGNED	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 h Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, Safety Valve: Manu. and Type by certify that the foregoing is true and correct CEPTED FOR RECORD OGER A. CHAPMAN BY	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM Set @
Spudde Lost i casing sx Th 8-6-8 three Reduce Drill Note: XC: Subsurface 18. I heret SIGNED R R APPROVED CONDITIONS	ed well with 12 1/4" hole on 8-2-81. H returns at 286'. Drilled to 1435'. Ra g set at 1435'. Cemented with 600 sx H ixset + 4% CaCl, tailed in with 200 sx 1. Cement did not circulate. Ran temp plugs with a total of 550 sx Thixset ed hole to 7 7/8", tested BOPs and cas ed ahead on 8-8-81. WOC total of 37 h Cement job witnessed by B. Jones/USG USGS (3), TLS, CEN RCDS, ACCTG, MEC, Safety Valve: Manu. and Type Dy certify that the foregoing is true and correct CEPTED FOR RECORD OGER A. CHAPMAN BY S OF APPROVAL, IF ANY:	Hit FW at 194' - TSTM. an 34 jts 8 5/8", 24#, K-55, HLW + 1# flocele + 4% CaCl, 300 "C" + 2% CaCl. PD at 4:30 PM p survey - TOC at 600'. Set + 4% CaCl. Circulated 40 sx. ing to 600 psi for 30 min - OK. ours. S. PARTNERS, ROWELL, FILE , REM Set @ IRDINATOBATEAUGUST 10, 1981 DATE

.

.