Form 9-331 C (May 1963)	UNIT DEPARTMENT	D.C.E. COPY ED STATES OF THE INTE SICAL SURVEY	SUBMIT IN TRI (Other instruct reverse sid	ATE on e)	Form approved. Budget Burenu No. 42-R1425. 30 - 005 - 61002 5. LEABE DESIGNATION AND SERIAL NO. NM 19825
			PEN, OR PLUG BA	ACK	6. IF INDIAN, ALLOTTIE OR TRIBE NAME
the second s		O DIALL, DELL			T. UNIT AGREEMENT NAME
1a. TYPE OF WORK DRI		DEEPEN 🗌	PLUG BAC	< □	A UNIT AUBBORDAT NAME
b. TYPE OF WELL			SINGLE MULTIPL	·	8. FARM OF LEASE NIME UN 2 3 1991
OIL GA WELL W 2. NAME OF OPERATOR	ELL X OTHER		ZONE ZONE	150	DORIS FEDERAL
	TROLEUM_CO.			1111 c	9. WELL NO.
3. ADDRESS OF OPERATOR		C.	ALE LANDER		10. FIELD AND POOL, OR WILDCAT
1000 V/	AUGHN BUILDING/M	IDLAND, TEXAS	198	<u> </u>	UNDESIGNATED ABO
At envface	eport location clearly and		Harris Core	and a second	11. SEC., T., B., M., OI: BLK.
• -)' FSL & 1980' F	EL			AND SURVEY OR AREA
At proposed prod. zon SAM	MF				SEC 14. T5S, R24E
14. DISTANCE IN MILES	AND DIRECTION FROM NEAR				12. COUNTY OB PARIE H 13. STATE
35 MILI	ES NORTH/NORTHEA	ST OF ROSWELL	NEW MEXICO	17. NO.	OF ACRES ASSIGNED
15. DISTANCE FROM PROPO LOCATION TO NEARES	r			TOT	160'
PEOPEETY OE LEASE I (Also to nearest drip	g, unit mue, m any /	0'/660'	640 PROPOSED DEPTH	20. ROT.	AEY OR CABLE TOOLS
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. N/A		A	4400'		ROTARY
OR APPLIED FOR, ON THIS LEASE, FT. N/A 4400 1 21. ELEVATIONS (Show whether DF, RT, GR, etc.)				22. APPROX. DATE YORK WILL START*	
3961.9					MAY 15, 1981
23.	Р	ROPOSED CASING A	ND CEMENTING PROGRA	M	
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH		QUANTITY OF CELENT
17 1/2"	13 3/8"	48#	800'		ulate to surface icient to iso ate wtr,o&g
11.	8 5/8"	24#	1600'		icient to cover all pay
7 7/8"	4 1/2			1	
surfac 1600'. not. using be run	e caisng. Will Will set 8 5/8 Will reduce hole	cement to sur 3" casing if w e to 7 7/8", i ud as requirec ith sufficient	face then reduce water zones have nstall ram type 1. After log eva t kinds and amoun	nole been e BOPs, luatic	deeper to set 13 3/8" to 11" and drill to encountered or omit if and drill to total depth on, 4 1/2" casing may isolate and seal off
			tern Pipeline Co		API
XC: IN ABOVE SPACE DESCRIF zone. If proposal is to preventer program, if a) drill or deepen direction	EN RCDS, ACCTO proposal is to deepen of ally, give pertinent dat	G, MEC, LAND, PAR or plug back, give data on p ta on subsurface locations as	TNERS resent pr nd measu	, FILE oductive zone and prorosed new productive red and true vertical depths. Give blowout
24.	1 WR	M		DD 711 / 1	TOD ADDIT 27 1001
BIGNED R.E.	Martin	TITLE_	REGULATORY COO	RDINA	TOR DATE APRIL 27, 1981
(This space for Do	PROVED ^{tice use)}		APPROVAL DATE		
PERMIE NO.	GEORGE H. STEW	NR T	. AIIBUTAN DATE		
APPROVED BYU CONDITIONS OF APPRO	N 2 2 1461	TITLE _			DATE
JAME	S A. GILLHAM CT SUPERVISOR	*See Instructio	ons On Reverse Side		

1

NE VEXICO OIL CONSERVATION COMMISS WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102 Supersedes C-128 Effective 1-1-65

All distances must be from the outer boundaries of the Section.

			Lease				Well No.
MESA	PETROLEUN		DOR	IS FEDE	¥****		<u>1</u>
Orat Letter	Section 14	5 SOUTH	Bange 24	EAST	County CH	IAVES	
Actual Footage Lo 1980	feet from the	EAST line and	760	foe	t from the	SOUTH	line
Bround Cevel Elev 3961.9			Foel	ESIGNATE	<u></u>		Dedicated Acreage: SE/4 160 Acres
	he acreage ded	icated to the subject v				marks on th	
	than one lease and royalty).	is dedicated to the we	ll, outline ei	ach and ide	ntify the o	ownership th	ereof (both as to working
	communitization	i, unitization, force-poo	ling. etc?				all owners been consoli-
[] Yes	No I	f answer is "yes," type	of consolida	tion			
	· .	he owners and tract des	criptions wh	ich have ac	tually be	en consolida	ited. (Use reverse side of
No allowa							nunitization, unitization,
forced-po- sion.	oling, or otherwi	se)or until a non-standa	rd unit, elim	inating suc	h interest	s, has been	approved by the Commis-
	 		1				CERTIFICATION
	-		}			(b aar b u a	ertify that the information con-
	ł		一流	2 2 5			ein is true and complete to the
			STATI		,	best of m	knowledge upd belief
	ł					Nome	
						R. E. MA	ATHIS
	j.			est f		Compony	DRY COORDINATOR
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			MESA PET	TROLEUM CO.
	l					MAY 8, 1	981
	I	- '	DSD	INC	'-		certify that the well location
	1	-	ן ז MM 1 98	325	-		this plat was plotted from field actual surveys made by me or
		—	1		-	1	supervision, and that the same nd correct to the best of my
	1	_]	know ledge	and belief.
	+				_]		
	1	_	<u>۱</u>	1980'		Date Survey	ed 4-1481
	ł		USI			Registered F sm:1/or 1. cand	Protessional Engineer
	l		- <u>- 1</u>		_	1 Con	millet
						Certificate P	THE ALE ALE ALE ALE ALE ALE ALE ALE ALE AL
G 330 860	•90 1320 1450	1980 2310 2640 20	00 1600	1000 8	00 G	ť	Ronald J. Eidson 323

APPLICATION FOR DRILLING

MESA PETROLEUM CO. DORIS FEDERAL #1 760' FSL & 1980' FEL, SEC 14, T5S, R24E CHAVES COUNTY, NEW MEXICO

LEASE NO: NM 19825

In conjunction with Form 9-331C, Application For Permit to Drill subject well, the following additional information is provided:

- Applicable portions of the <u>GENERAL REQUIREMENTS FOR OIL AND GAS</u> <u>OPERATIONS ON FEDERAL LEASES</u>, Roswell District, Geological Survey of September 1, 1980 will be adhered to.
- 2. Geological markers are estimated as follows:

.

SEVEN RIVERS	SURFACE
SAN ANDRES	632'
GLORIETTA	1472'
TUBB	2972 '
ABO	3612'
HUECO	4372 '

- 3. Hydrocarbon bearing strata may occur in the Abo formation. No fresh water is expected to be encountered below 1000'.
- 4. The Casing and Blowout Preventer Program will be determined by hole conditions as encountered. Anticipate drilling with air or foam using ram type preventer and rotating head for well control. The 13 3/8" casing will be set at approximately 800' to protect any fresh water zones and cemented to the surface. The 8 5/8" casing will be set at approximately 1600' if water zones have been encountered or omitted if not and ram type preventers installed. Sufficient amounts and kinds of cement would be used to ensure any water, gas, or oil zones encountered are isolated and shut off down to the casing point if run. The 4 1/2" production casing will be set at total depth or shallower depending upon the depth of the deepest commercial hydrocarbon bearing strata encountered.
- 5. No drillstem tests or coring program is planned. The logging program may consist of a GR-CNL from surface to total depth and FDC from casing point to total depth.
- 6. Anticipated drilling time is fifteen days with completion operations to follow as soon as a completion unit is available.

MULTI-POINT SURFACE USE AND OPERATION PLAN

MESA PETROLEUM CO. DORIS FEDERAL #1 760' FSL & 1980' FEL, SEC 14, T5S, R24E CHAVES COUNTY, NEW MEXICO

LEASE NO: NM 19825

This plan is submitted with the Application for Permit to Drill the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operational plan in both the actual and post drilling-completion operations.

- 1. Existing Roads
 - A. Exhibit I is a portion of a highway map showing the location of the proposed well as staked. The proposed well is approximately 30 miles north of Roswell, New Mexico.
 - B. Directions: Travel north of Roswell on US Highway 285 to mile marker 139. Turn east on county road for 12 miles (3/4 mile past Stancel Fed #1 lease road) then northwest on 2 track for 4/10 mile to the location.

2. Planned Access Road

A. Length and width: The new access road will be 12' wide (16' ROW) and approximately 4/10 mile of upgraded 2-track.

(See Exhibit II)

- B. Construction: The new road will be constructed by grading and topping with compacted caliche. The surface will be crowned, with drainage on both sides. (See Exhibit III)
- C. Culverts, Gates and Cattleguards: One cattleguard will be recuired.
- D. Cut and Fill: In order for the location to be level, approximately 5' of cut from the south side will be moved to form the pit.

3. Location of Existing Wells

Existing wells within a one-mile radius are depicted by Exhibit IV.

4. Location of Existing and/or Proposed Facilities

If the well proves to be commercial, the necessary production facilities, gas separation-process equipment and tank battery, will be installed on the drilling pad.

Multi-Point Surface Use and Operation Plan

Page 2

5. Location and Type of Water Supply

It is planned to drill the proposed well with air. If water is needed, it will be obtained from commercial sources and will be trucked to the wellsite over the existing roads and the proposed access road shown on Exhibits I and II or piped in by temporary line from a nearby source.

6. <u>Source of Construction Materials</u>

Caliche for surfacing the road and the wellsite pad will be obtained by the dirt contractor from the Federal Government or private sources. Top soil from the location will be stockpiled near the location for future rehabilitation use. No surface materials will be disturbed except for those necessary for the actual grading and leveling of the drillsite and access road. Probable pit is located: NE/4, Sec 22, T5S, R24E.

- 7. Methods of Handling Waste Disposal
 - A. Drill cuttings will be disposed of in the reserve pits.
 - B. Drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry.
 - C. All pits will be fenced with normal fencing material to prevent livestock from entering the area.
 - D. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or separate disposal application will be submitted to the USGS for approval.
 - E. Current laws and regulations pertaining to the disposal of human waste will be complied with.
 - F. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
 - G. All trash and debris will be buried or removed from the wellsite within 30 days after finished and/or completion operations.
- 8. Ancillary Facilities: None required.
- 9. Wellsite Layout:
 - A. Exhibit V shows the relative location and dimensions of the well pad, reserve pits, and major rig components. The pad and pit area has been staked and flagged.
 - B. Some leveling of the wellsite will be required. See Exhibit II: for additional details.
 - C. The reserve pit will be plastic lined.

Multi-Point Surface Use and Operation Plan

Page 3

- 10. Plans for Restoration of the Surface:
 - A. After completion of drilling and/or completion operations all equipment and other material not needed for operations will be removed. Pits will be filled and location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing a condition as possible.
 - B. Any unguarded pits containing fluids will be fenced until they are filled.
 - C. If the proposed well is non-productive, all rehabilitation ard/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment, if drying conditions permit.
- 11. Other Information:
 - A. Topography: The land surface in the vicinity of the wellsite is gently sloping to the northeast.
 - B. Soil: The topsoil at the wellsite is sandy loam.
 - C. Flora and Fauna: The vegetative cover consists of Tabosa and other prairie grasses, creosote bush, yucca, cactus, prairie flowers and other miscellaneous desert growth. Wildlife in the area probably includes those typical of semi-arid desert land. The area is used for grazing.
 - D. Ponds and Streams: Huggins Draw is 1/2 mile to the north.
 - E. Residences and Other Structures: There are no residences or other structures in the vicinity of the proposed well.
 - F. Land Use: Grazing.
 - G. Surface Ownership: The wellsite is on Federal surface.
 - H. There is no evidence of any major archaeological, historical, or cultural sites in the area. NMAS, Inc. has conducted an archaeological study of this site and provides this report to interested parties.

Multi-Point Surface Use and Operation Plan

Page 4

- 12. Operator's Representatives:
 - A. The field representatives responsible for assuring compliance with the approved surface use and operations plan are as follows:

J. James	M. P. Houston
P. O. Box 298	1000 Vaughn Building
Roswell, New Mexico	Midland, Texas 79701
(505-623-0989 Unit #4039)	(915-683-5391) - Office
•	(915-694-3442) - Home

13. Certification

I hereby certify that I, or persons under my direct supervision, nave inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge true and correct; and, that the work associated with the operations proposed herein will be performed by Mesa Petroleum Co. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

April 27, 1981

Michael P.

Michael P. Houston Operations Manager







•			O.A. Elañeba		
t	0.5 0.5 1.5 1.5 1.5	<u> </u>	24 11 5. Elaniche Triae W.C. Kaufmon	Yotes Part Vates Ant	<u> </u>
-1-6J 19:31		10-1-0) 70178	4 (50 94153	12-1-00 24612 L6 995 27¢	N.8 Colling 6 - 1 - 82
9	Asome Act, 12 M 	21	- 22	23	24
	Yotes				
U. 5.	U.S	U.S. P.W_suglice	<i>U</i> . \$	U.S. Sighe	Stote
-	A Storman White a White a Annual Storman	W.C.Koufmen 4 + 1 - 83 86183	Yotes 8 - 1 - 87	' Yales Apr. 7- 3 - 87 Yotos LE" 375	W.S.Colling 6 + 1 + 82 45 242
Je. 	Yates Pet. GW Secre 12 - 1 - 00 T. J. Secre L. T. Lewis		****	6-1-87 30860 775	30
□] >¥. ■	29				
	10174 10-64 30 43 10 TA G. 7 A		•	66 \$16 27 ¢	LE 710 319
<u>s.</u>	Yotes 5.1.09	U.S. Yotes	U.S. W.J. Keufmon 4-1 - 83	U.S. State Votes Pet.	s State W.B.Collins
1 <u>c</u>	16-611 310	10 × 1 × 83 • 19172	36153	7-1-42 Vetes L6 866 8-1-87 276 80000	6-1-82 L6-230 312
Adoms 1 Reh. Yz Mine. Sarre	32			35	36
cradr. h Francis rs Pet		12 - 1 - 85 24813 Vares 6-1-11 Locatio	3 · 1 · 67 5·1·64 77390 30660 2030		r
1 - 65 16(3	Stole	State U.S.	U.S.		stote
, 1779 87		J.J. Grynberg 9.1.87 9 • 1 • 52 9.1.87 16-544 1 472 45	M J.Horvey,Jr. 9 · 1 · 04 22 6 · 6	L L	J.J. G. d. horry J 9-1-92 LG 529 Stole 476 5101e 476 5101e 476 5101e 476 5101e 476 5101e 476
	173. Adores	M.J. Horvey, Je 9-1-02 51010 2264 A 51010	Juin Grynerig Litet Store	2	2
i .			Yotes		4.14-57
	G.M. Sacro T. A. Sacra, Jr. C.L. Francisty U.S.	<i>v.s</i> .		MESALDOENICK	All Signa U.S. J.W.Corn
5. 		(Meseria	H.B	
: 614	0	Ast Actives	TISTS NOT UNITED STATES	elol 40.1 N. Clore Va Terman Blylbe 118 - 1	Hing I J W Corn Slole
s.	BUCALACA	U.W. Schesleding J.W. Lonning	Lillie Yoterst Then Ps	The STON Basel	/ MELA 12
Adoms Rch.Vz M.L. Secre		2265 X/ESA - 00-3 7/CA-0100	30841	HILSO INFER	Schutzers Sites
rendis	- 81	• 51	U.S. 2785 400	(hilling to be a set of the set o	Siele Siele
1- 04 54	131242 231242 2329	J.J.Grynberg 9 + 1 + 82 68-566 47 ¢	Frank and I has some if	30091 1.8-54 74 7 1987	4427
3	1.5. U.S. 1540	16	Little Yotes		13
	time 10 BELL			J. H. Syntery Lern 1. 52 MESA	
Lillie Yotes Joool U.S.	1-1, 10 2 132 5-	sieie 5	24. J.W. Corn	Vates Q FE	DERAL S.P. Journson Jr. Salar J. W. Torn, cial U.S.
Little Vetes	Yøtes 2 - 1 - 80 11103	Yetes 2. 1. 82 14983	J.W. J. 1. 22	1.1.47 1.1.47 1.1.47	10-1+ BO
5.			- 0004 +2 54 W	ELFEDIDAL	
	20	21	MESA 22 #35700 - FEDERAL	17 0 ·	24
North 232	U.S. Multion Ve.Jr J.W.Corn J.W.Corn V.S		399	The spend	His stall
Keith Unruh	J.W.Com 22614 C.B.Grofe J.J. Grynberg	U.S. Yotes	• 51 U.S : - 500 Yates 2. 1 : 82	J.R. UI	
12-1-62 17034 .	10391 (1882	2 · 1 · 62 14363	14 9 8 3	<u>Herry Cur</u> Yotes	Licelai J.W. Corn Yetes
1	HEYates IRR Schner	28	27	26	25257 Senders 25 Senders 5 Sanders
2+++ 0 9 3+639	29610 .1 20403				18 533 66 788 61 61 81 9 61 61 81 9 61 71 - 58
	U.S.	<i>u</i> .s.	US. Yates	A B	
		MJ Horvey Jr S - 1 - 79	2 - 1 - 82 14983		TROLEUM CO.
H E Yates 4-1-87 20010	J.J.Grynberg B • 1 • 82 16-5000	9394	•		
H E Yores 4 - 1 - 87 20010	8 - 1 ⁻ 82 <u>16-546</u> 47¢		34		HIAN BASIN DIVISION
4;;;;;}	8 - 1 - 82 36-36	9394	34	PER	IBIT IV
4:::87 	•.1:48 16:544 41¢ 32	9398 	34 U.S.	EXH ONE-MILE R	IBIT IV ADIUS LAND MAP FOR
4:1:07 2:0010 Gr,nberg 3:1:00 0:052	32 Stole	9398 	U.S.	EXH ONE-MILE R	IBIT IV
4:1:07 2:0010 Gr,nberg 3:1:00 0:052	32 5101e MESQ - 6 	9398 	U.S.	EXH ONE-MILE R	IBIT IV ADIUS LAND MAP FOR



400'

÷.

