

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒
well well other
-
2. NAME OF OPERATOR
MESA PETROLEUM CO. ✓
-
3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17
below.)
AT SURFACE: 760' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME
-
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- | | |
|-----------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> |
| (other) 4 1/2" CSG & CEMENT | |

SUBSEQUENT REPORT OF:

- 11111111

RECEIVED
(NOTE: Re
JUL 24 1981 CH)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM 19825
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
JUL 29 1981
DORIS FEDERAL
9. WELL NO.
O. C. D.
1 ARTES A, OFFICE
10. FIELD OR WILDCAT NAME
UNDESIGNATED ABO
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC 14, T5S, R24E
12. COUNTY OR PARISH
CHAVES
13. STATE
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3961 9' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to TD of 4431' on 7-21-81. Ran 101 jts 4 1/2", 10.5#, K-55 casing set at 4431'. Cemented with 650 sx HLW + 10# salt + 1/4# floccle, tailed in with 450 sx 50-50 Pozmix + 8# salt + 2% gel + 3/10% CFR-2. PD at 11:30 AM 7-22-81. Circulated 25 sx. Released rig at 6:00 AM 7-23-81. WOCU estimated to arrive 8-3-81.

XC: USGS (3), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, FILE

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

- 18. I hereby certify that the foregoing is true and correct**

SIGNED R. P. [Signature] TITLE REGULATORY COORDINATOR DATE JULY 23, 1981

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL CHAPMAN

TITLE _____ DATE _____

JUL 27 1981

U.S. GEOLOGICAL SURVEY
SOUTH, NEW MEXICO

See Instructions on Reverse Side