Form 9-331	Form Approved. Budget Bureau No. 42–R1424		
Dec. 1973 UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	NM - 19825		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME DORIS FEDERAL		
1. oil gas x other well other	9. WELL NO. ARTESTATOR		
2. NAME OF OPERATOR MESA PETROLEUM CO.	10. FIELD OR WILDCAT NAME UNDESIGNATED AB0		
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701	11. SEC., T., R., M., OR BLK. AND SURVEY CR		
<ul> <li>4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> </ul>	SEC 14, T5S, R24E		
AT SURFACE: 1980' FNL & 1880' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH CHAVES NEW MEXI 20		
AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		
16. CHECK APPROPRIATE DOX TO INDIGITE THE REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL			
			change on Form 9–330.)
	1년 31년 동방동V법이 2017년 1월 2017년 1		
	elv Mexico 이 가운데 전 등일에 한 물을 했다.		
ABANDON* TD 4 1/2" csg & cement	· · · · · · · · · · · · · · · · · · ·		
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> </ol>	nt to this work.)*		
Drilled 7-7/8" hole to TD of 4350' on 8-15-81. Ran 99 jts 4 1/2", 10.5#, K55 casing set at 4033'. Cemented with 650 sx HLW + 10# salt + 1/4# flocele and tailed in with 450 sx 50-50 pozmix + 8# salt +			
		1/4# flocele and tailed in with 450 sx 50-3	5-81 Cement did not
2% gel + 3/10% CFR-2. PD at 9:00 p.m. 8-16-81. Cement did not circulate. Released rig at 6:00 a.m. 8-17-81. WOCU estimated to arrive 8-31-81.			
		XC: USGS (3), TLS, CEN RCDS, ACCTG, MEC, LAND, Subsurface Safety Valve: Manu. and Type	Set @ Ft.
		18. I hereby certify that the foregoing is true and correct	RDINATOBATE 8-17-81
		SIGNED KECORS	
APPROVED BY ALLO O TITLE DATE			
CONDITIONS OF APPRILLE AF AN 1981			
U.S. GEOLOGICAL MERINE			
ROSWELL, NEW MARKED See Instructions on Reverse Side			

t 3

F