

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		2. Unit Agreement Name
3. Name of Operator MESA PETROLEUM CO.		4. Farm or Lease Name COMER
5. Address of Operator 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701		6. Well No. 3
7. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>NORTH</u> LINE AND <u>660</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>17</u> TOWNSHIP <u>5S</u> RANGE <u>25E</u> NMPM.		8. Field and Pool, or Wharft UNDESIGNATED ABO
9. Elevation (Show whether DF, RT, GR, etc.) 3842.7' GR		10. County CHAVES

11. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well with 17 1/2" hole on 7-25-81. Hit fresh water at 83' - TSTM. Drilled to 863' and ran 23 jts 13 3/8", 48#, H-40 casing set at 860'. Cemented with 750 sxs HLW + 1# flocele + 4% CaCl, 200 sx Thixset + 4% CaCl, and tailed in with 200 sx C + 2% CaCl. PD at 4:00 AM 7-27-81. Cement did not circulate. Ran temp survey - TOC at 475'. Set two plugs with a total of 400 sx Thixset + 4% CaCl. Circulated 25 sxs. Reduced hole to 11" and drilled ahead on 7-27-81. WOC total of 19 hours.

(NOTE: Quit dusting at 900' - fluid TSTM.)

XC: NMOCD (3), TLS, CEN RCDS, ACCTG, ROSWELL, MEC, LAND, PARTNERS, FILE

13. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. P. Mathis TITLE REGULATORY COORDINATOR DATE 7-28-81

APPROVED BY Mark Wilkin TITLE OIL AND GAS INSPECTOR DATE AUG 06 1981

CONDITIONS OF APPROVAL, IF ANY: