

N.M.O.C.D. COPY

SF/file

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ gas ☒ other ☐  
well well
2. NAME OF OPERATOR  
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FSL & 660' FEL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- TEST WATER SHUT-OFF ☐ ☒
- FRACTURE TREAT ☐ ☐
- SHOOT OR ACIDIZE ☐ ☐
- REPAIR WELL ☐ ☐
- PULL OR ALTER CASING ☐ ☐
- MULTIPLE COMPLETE ☐ ☐
- CHANGE ZONES ☐ ☐
- ABANDON\* ☐ ☐
- (other) ☐ ☐

5. LEASE NM-9813
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
South Alkali "LK" Federal
9. WELL NO.  
2
10. FIELD OR WILDCAT NAME  
Und. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P  
Sec. 1-6S-25E
12. COUNTY OR PARISH Chaves 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3799.5' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 15" hole at 3:00 PM 7-17-81.  
TD 840'. Ran 21 jts of 10-3/4" 40.5# K-55 ST&C (841') of casing set at 840'.  
1-Texas Pattern guide shoe at 840'. Flapper insert float at 800'. Cemented  
w/815 sacks Class "C" 3% CaCl. PD 2:15 AM 7-19-81. Bumped plug to 500 psi,  
released pressure and float held okay. Cement circulated 50 sacks. WOC 14 hrs  
and 45 minutes. Reduced hole to 7-7/8". Drilled out and resumed drilling.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Engineering Secty DATE 7-21-81

APPROVED BY \_\_\_\_\_ (This space for Federal or State office use)  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

ROGER A. CHAPMAN

JUL 28 1981

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side  
ROSWELL, NEW MEXICO