Drawer DD

Artesia, NM 88210

Form Approved.

Form 9-331 Dec. 1973

Dec. 1973			Budget Bu	reau No. 42-R142	4
UNITED STATES		5. LEASE	Tea A	<u> </u>	_
DEPARTMENT OF THE INTERIOR		NM 36645			_
GEOLOGICAL SURVI	6. IF INDIAN, A	LLOTTEE OR	TRIBE NAME		
SUNDRY NOTICES AND REPO	RTS ON WELLS	7. UNIT AGREE	MENT NAME	<u> </u>	_
(Do not use this form for proposals to drill or to deep reservoir, Use Form 9-331-C for such proposals.)				를 맞이었 한 보고 # 3 **	_
1 eil ger	CEIVED BY	8. FARM OR LE HUB FEDERAL		2 (5 fb) 2 (7 fb)	
well well other		9. WELL NO.			
2. NAME OF OPERATOR MESA PETROLEUM CO.	20 1987	10. FIELD OR W			_
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING MIDLAND	. C. TEXAS_7970	UNDESIGNATE		AND SURVEY (OR
4. LOCATION OF WELL (REPORT LOCATION		AREA SEC 24, T85	200	-95-	
below.) AT SURFACE:	1000 /r	12. COUNTY OF		STATE	<u>-</u>
AT TOP PROD. INTERVAL:	1980/E	CHAVES		MEXICO	
16. CHECK APPROPRIATE BOX TO INDICAT	E NATURE OF NOTICE.	14. API NO.	- 등 최 최 성 - 최 집 3 1분		
REPORT, OR OTHER DATA		15. ELEVATION	S (SHOW DF,	KDB, AND W	
REQUEST FOR APPROVAL TO: SUBSE	QUENT REPORT OF:	3950.6 GR	<u>tangan</u> Tanggan	<u> </u>	_
TEST WATER SHUT-OFF		99 mm			
FRACTURE TREAT		初仍回回			
REPAIR WELL		(NOTE: Report re	sults of multiple	completion or zo	one
PULL OR ALTER CASING	SEP 2		n_Form:9-330.)	를 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등	e)
MULTIPLE COMPLETE		1001			- T
ABANDON*	区	GAS			1
(other)	ROSWELL, N	EW MEXICO			Net
17. DESCRIBE PROPOSED OR COMPLETED Concluding estimated date of starting any properties and true vertical depths for all n	PERATIONS (Clearly state proposed work. If well is designed to the state of the sta	e all pertinent det irectionally drilled.	ails, and give	pertinent date ace locations a	es, nd
Commenced P&A Operations or	n 9-17-81 as follo	ws:			
Pumped 250 sx HLW + 4% CaCl	+ 1# Flocele at	top of fish	600 ·.	Forms of the particular particula	
Pumped 200 sx HLW + 4% CaCl	470'.		Sicari Mana M Sicari M Sicari		
Pumped 200 sx HLW + 4% Ca(• -	- (5 년 -) [설년 :			
·					
Pumped 200 sx HLW + 4% CaCl	+ 150 DCD "C" +	2% CaCl @ 190	J' to sur	face.	
Install Dry Hole Marker. W	lell P&A'd 9-18-8	1.			
XC: USGS (6), TLS, CEN RCDS, A Subsurface Safety Valve: Manu. and Type	CCTG, MEC, KAND,	PARTNERS, RO	OSWELL, FI Set@_		Ft.
18. I hereby certify that the foregoing is true ar	nd correct		· · · · · · · · · · · · · · · · · · ·		
SIGNED R.S. Mark	TIREGULATORY COORD	INATOBATE SI	EPTEMBER 2	22, 1981	
	space for Federal or State of	Dord "		OVED CHESTER	_\ -
CONDITIONS OF APPROVAL, IF ANY: Jephilles as to plugging of the well bear.					- 1
Surface	under bond is retained un restoration is completed.	til	FEB 1	1 1987	

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT