	ULFANI	MENT		A CONTRACTOR OF A CONT	1		
	•		CONSERVA	TIONRECEISEONEY			
DISTRIBUTION			Р. О. ВОХ	< 2088		Form C-103	
SANTA FE		S/	ANTA FE, NEW	MEXICO1875911984	ł	Revised 10-1-78	
FILE	L	\checkmark		JUE 09-1304	Sa. Indicate Typ	e of Lease	
U.S.O.S.				O, C. D.	State	Fee X	
LAND OFFICE							
OPERATOR	/]		ARTESIA, OFFICE	5, State Otl & G	as Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS .)						IIIIIIIII	
		OTHER-			7. Unit Agreeme	ni Name	
Name of Operator						8. Farm or Lease Name	
Yates Petroleum Corporation 🗸					Snell "	QZ''	
Address of Operator					9. Well No.	· · · · · · · · · · · · · · · · · · ·	
		a	NR 00010		1		
207 Sou	th 4th	St., Artesia	NM_88210		10. Field and Pa	ool, or Wildcat	
		((0)		1000	Here Door	s Slope Abo	
UNIT LETTER <u>C</u>	· •	FEET PI	ROM THE NOTTH	LINE AND PEET PR	DM		
			_				
West	_ LINE, SE	ст10N <u>31</u>	_ TOWNSHIP6S	RANGE 25E · NMP	**• {\\\\\\\\\\\		
	/////	15. Ele	evation (Show whether L		12. County		
	./////		3911-	₽' GR 390212	Chaves		
	Chec	k Appropriate B	or To Indicate N	ature of Notice, Report or C	ther Data		
NOT		INTENTION TO:		-	NT REPORT OF		
		INTENTION TO.	·	308324021	AT REPORT OF:	•	
						 1	
ERFORM REMEDIAL WORK	_	PI	LUG AND ABANDON	REMEDIAL WORK	ALTER	AING CASING	
EMPORARILY ABANDON	_			COMMENCE DRILLING OPNS.	PLUG >	AND ABANDONMENT	
ULL OR ALTER CABING		Ci	HANGE PLANS	CASING TEST AND CEMENT JOB	0		
				OTHER Intermediate	Casing	X	
OTHER							

7. Describe Proposed or Completed Operations (Clearly state all pertinen work) SEE RULE 1903.

Ran 40 jts of 7" 23# and 20# J-55 casing as follows: 20 jts 7" 23# J-55; 18 jts 7" 23# J-55; 2 jts 20# J-55; casing set 1600'. 1-Texas Pattern notched guide shoe set 1600'. Insert float set 1556'. Cemented w/350 sacks Pacesetter Lite with 10#/sack Hiseal, 3#/sack Perma-check, 1/4#/sack celloseal and 3% CaCl2. Tailed in w/200 sacks Class "C" 2% CaCl2. Com-pressive strength of cement - 1250 psi in 12 hrs. PD 1:00 AM 7-4-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement 990'. Ran 1". Tagged cement 990'. Spotted 100 sacks Class "C" 4% CaCl2. PD 8:30 AM 7-4-84. WOC 2 hrs. Tagged cement at 840'. Redi-Mixed to surface with 8 yards. WOC. Drilled out 1:00 AM 7-5-84. WOC 24 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 6-1/4". Drilled plug and resumed drilling.

)	Original Signed By Leslie A. Clements	JUL 0 6 1984
into fly an	The Quality	Production Supervisor	7-5-84
. I hereby certify that	the information above is true and comp	lete to the best of my knowledge and belief.	