

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2084
SANTA FE, NEW MEXICO 87501
AUG 22 1984
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM

THE West LINE, SECTION 31 TOWNSHIP 6S RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Snell QZ

9. Well No.
1

10. Field and Pool, or Wildcat
Undr Pecos Slope Abo

15. Elevation (Show whether DF, RT, GR, etc.)
3878.2' GR

12. County
Chaves

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Production Casing, Perforate, Treat ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 4000'. Ran 92 jts of 4-1/2" 9.5# J-55 casing set 4000'. Regular guide shoe set 4000'. Float collar set 3947'. Cemented w/275 sx Class "C", .5#/sx Hiseal, .5% CF-1, .2% AF-S and 2% KCL. Compressive strength of cement - 950 psi in 12 hrs. PD 10:15 PM 7-15-84. Bumped plug to 1000# for 30 minutes, held OK. WOC 18 hours. WIH and perforated 3626-3820' w/28 .50" holes at 2 SPF as follows: 3626, 28, 30, 32, 34, 74, 3792, 94, 3810, 12, 14, 16, 18 and 20'. Acidized perfs 3792-3820' (16 holes) w/3000 gal 7 1/2% acid and ball sealers. Acidized perfs 3626-74' (12 holes) w/2000 gal 7 1/2% acid and ball sealers. Frac'd perfs 3626-3820' (28 holes) w/60000 gal gelled 2% KCL water, 120000# 20/40 sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Luanita Goodlett

TITLE Production Supervisor

DATE 8-22-84

PROVED BY Mike Williams

TITLE OIL AND GAS INSPECTOR

DATE AUG 24 1984

CONDITIONS OF APPROVAL, IF ANY: