NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

| | FIE | LD REPORT | FOR CEMENTING | ; <u>of</u> | WELLS | | | | |
|---|---------------------------------------|---------------------|--------------------|-------------|--------------|---------------|---------------|--------|--|
| Operator Yetes Petr Corp Lease Conejo RH State | | | | | | Well # | | | |
| Location of Well 640 | Unit | Section | Townsh 7 | | Range Z S | County Che | | | |
| Drilling Contractor La Rue #1 Type of Equipment Potary ASAP | | | | | | | | | |
| * witness | | APPROV | ED CASING PRO | | • | | · · · · · · | | |
| Size of Hole- | Size | of Casing | Weight Per Foot | Nëv | v or Used | Depth | Sacks | Cement | |
| 171/2 | 1 | 33/8 | 43# J-55 | | | 900 ' | 200 SX | Circ | |
| 7 7/8 | 51/2 | 05 4 ^{1/2} | 15.5# - 10.5# | | | 4500 | 400 SX | ! | |
| - | | | | | | İ | | | |
| Casing Data: | | | | | | | | | |
| Surface joints of inch # Grade | | | | | | | | | |
| (Approved) (Rejected) | | | | | | | | | |
| Cenenting Program | | | | | | | | | |
| Size of hole 15" Size of Casing 103/4" Sacks coment required | | | | | | | | | |
| Type of Shoe used and Float collar used meet Btm 3 jts welded us | | | | | | | | | |
| TD of hole 900 Set 900 Feet of 103/4"Inch 38 # Grade K-SS | | | | | | | | | |
| NewJused csg. @ 900' with 800 3% sacks near coment around shoe | | | | | | | | | |
| Plug down @_3:15additives | | | | | | | | | |
| Cement circulated Up No. of Sacks 35 sx | | | | | | | | | |
| Cemented by Western Cementing Witnessed by Western Cementing | | | | | | | | | |
| Temp. Survey ran @(AM) (FM) Datetop cement @ | | | | | | | | | |
| Casing test @ | - | (AM) (P | M) Date | | | | | | |
| Method UsedWitnessed by | | | | | | | | | |
| Checked for s | | | · · · · · | | | | | | |
| Nethod usedWitnessed by | | | | | | | | | |
| Remarks: | | | | | | <u>,,,,,</u> | , _, _, _, _, | | |
| | · · · · · · · · · · · · · · · · · · · | | • | | Las | t drly. In | eak D | 728' | |
| | Full returns | | | | | | | | |