

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL & GAS COMMISSION
STANDARD INSTRUCTIONS ON PERMIT APPLICATIONS
Artesia, NM 88210

Form approved.
Budget Bureau No. 42-R1424.

C/SF

5. LEASE DESIGNATION AND SERIAL NO.

NM-39127

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this for a for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> P&A		RECEIVED	
2. NAME OF OPERATOR Yates Petroleum Corporation		OCT 29 1981	
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210		O. C. D. ARTESIA, OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 860' FWL of Section 24-T5S-R25E		32	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3718.5' GR	9. WELL NO. 1	10. FIELD AND POOL, OR WILDCAT Wildcat Abo
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit L, Sec. 27-5S-25E	12. COUNTY OR PARISH Chaves
		13. STATE NM	

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon this well as follows:

- 1) Spot 35 sacks Class C cement plug through drill pipe from 4295-4395' (Wolfcamp top @4345').
- 2) Spot 35 sacks Class C cement plug through drill pipe from 3627-3737' (Abo top @3677').
- 3) Spot 35 sacks Class C cement plug through drill pipe from 1580-1670' (Glorieta top @1630').
- 4) Spot 35 sacks Class C cement plug through drill pipe from 877-977' (10-3/4" surface casing shoe at 927').
- 5) Set 25 sacks cement surface plug.
- 6) Install regulation abandonment marker.
- 7) Surface is federally owned and will be restored in accordance with USGS-BLM requirements.

Verbal approval for this plugging program was given by Mr. Jim Gillham, USGS, Roswell on 10-12-81.

RECEIVED
OCT 15 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert K. Hall

TITLE

Engineer

DATE

10-13-81

(This space for Federal Permit Application Use)

APPROVED BY (Orig. Sgd.) ROGER A. CHAPMAN

CONDITIONS OF APPROVAL, IF ANY:

OCT 19 1981

JAMES A. GILLHAM
DISTRICT SUPERVISOR

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

*See Instructions on Reverse Side