

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other Plugback & test San Andres
2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL & 860' FWL, Sec. 27-5S-25E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input checked="" type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Production Casing <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Decision was made to test the San Andres before plugging well. Plugged well back to 3627' as follows: Plugs set 10-13-81:

Plug #1: 4395-4295' (Wolfcamp) - 35 sx 50/50 Poz Class "C" cement.  
Plug #2: 3727-3627' (Abo) - 35 sx 50/50 Poz Class "C" cement.

TD 4450'; PBTD 3627'. Ran 45 joints of 5-1/2" 14# casing set at 1926'. Float shoe at 1926'. Cemented w/350 sacks Class C 2% CaCl<sub>2</sub>. PD 5:15 PM 10-19-81. Bumped plug to 1400 psi, released pressure & float held okay. WOC.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Engineering Secty DATE 10-21-81

APPROVED BY \_\_\_\_\_ (space for Federal or State office use)

APPROVED BY \_\_\_\_\_ (ORIG. SGD.) DAVID R. GLASS

CONDITIONS OF APPROVAL

DEC 20 1982

MINERALS MANAGEMENT SERVICE  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

5. LEASE NM-39127

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Doris RI Federal

9. WELL NO. 1

10. FIELD OR WILDCAT NAME  
Wildcat Abo SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit L-Sec. 27-T5S-R25E

12. COUNTY OR PARISH Chaves

13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3718.52 GR

(NOTE: Report results of multiple completion or change in Form 9-330.)

RECEIVED

DEC 21 1982

ROSWELL, NEW MEXICO