| Form 9-331 Dec. 1973 UNITED STATES Artesla, IN DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY | Form Approved. Budget Bureau No. 42-R1424 5. LEASE NM 11799 6. IF INDIAN, ALLOTTEEOR TRIBE NARECEIVED | |
|---|--|--|
| GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil gas well other 2. NAME OF OPERATOR Yates Petroleum Corporation 3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)1980' FNL & 660' FWL, Sec. 9-7S-25E AT SURFACE: AT TOP PROD. INTERVAL: | 6. IF INDIAN, ALLOTTELIOR TRIBE NAME CEIVED 7. UNIT AGREEMENT NAME FEB 2.4 1982 8. FARM OR LEASE NAME Hahn NH Federal O. C. D. 9. WELL NO. 3 ARTESIA, OFFICE 10. FIELD OR WILDCAT NAME Pecos Slope-Abo Gas 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit E, Sec. 9-T7S-R25E 12. COUNTY OR PARISH 13. STATE Chaves NM | |
| AT TOTAL DEPTH: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3842' GR 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and | | |
| Spudded a 14-3/4" hole at 7:30 PM 1-31-82. Ra at 832'. 1-Texas Pattern guide shoe at 832'. w/400 sacks Pacesetter Lite "C" 3% CaCl ₂ . Ta: with 3% CaCl ₂ . PD 6:40 AM 2-2-82. Bumped plu and float held okay. Cement circulated 50 sac 2-3-82. WOC 18 hours. Nippled up and tested to 9-7/8". Drilled plug and resumed drilling. | an 22 joints of 10-3/4" casing Insert float at 789'. Cemented iled in w/300 sacks Class "C" ug to 1000 psi, released pressure cks. WOC. Drilled out 12:40 AM to 1000 psi, okay. Reduced hole | |

. . .

| Subsurface Safety Valve: Manu. and Type | |
|--|-------------------------------------|
| 18. I hereby certify that the foregoing is true and co | rrect |
| SIGNED Samela and Calific TITL | EEngineering Secty Date 2-12-82 |
| , (This spa | ce for Federal or State office use) |
| APPROVED, BYCEFTED FOR RECORD | ce for Federal or State office use) |
| FEB 1 9 1982 | |

*See Instructions on Reverse Side

. .

U.S. GEOLOGICAL SURVEY

143 C 2