- E. Trash, waste paper, garbage, and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind. Location of the trash pit is shown on Exhibit "C".
- F. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.

8. ANCILLARY FACILITIES:

A. None necessary

- 9. WELL SITE LAYOUT:
 - A. Exhibit "C" indicates the relative location and dimensions of the well pad, mud pits, reserve pit and major rig equipment.
 - B. The location is sloping to the north requiring about a 3' cut on the south side.
 - C. The reserve pit will be lined with plastic to prevent loss of water.

10. PLANS FOR RESTORATION OF THE SURFACE:

- A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed. Pits will be filled and the location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing condition as possible.
- B. Any unguarded pits containing fluids will be fenced until they are filled.
- C. If the well is non-productive the disturbed area will be rehabilitated to Federal agency requirements and will be accomplished as expeditiously as possible.

11. OTHER INFORMATION:

A. <u>Topography</u>: The topography is a gently rolling plain, sloping to the north in the vicinity of of the drill pad and access road.

