5. LEASE

UNITED STATES

DEPA	RTMENT OF THE INTERIOR	NM-27634 6. IF INDIAN, ALLOTTEE OR TRIBE NAME						
CISF	GEOLOGICAL SURVEY							
SUNDRY NOT	TICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME RECENSED						
reservoir. Use Form 9-331	proposals to drill or to deepen or plug back to a different —C for such proposals.)	8. FARM OR LEASE NAME						
1. oil gas		HANAGAN FEDERAL OCT 1 3 1981						
well well	⊠ other	9. WELL NO.						
2. NAME OF OPERA		0.00						
Stevens Ope	rating Corporation /	10. FIELD OR WILDCAT NAME						
3. ADDRESS OF OP	PERATOR	Wildcat						
P. O. Box 2	203, Roswell, New Mexico 88201	11. SEC., T., R., M., OR BLK. AND SURVEY OR						
4. LOCATION OF WI	ELL (REPORT LOCATION CLEARLY. See space 17	AREA						
below.) 990' F	NL, 1980' _{SEEL} , Sec. 14-7S-26E	Sec. 14-7S-26E 12. COUNTY OR PARISH 13. STATE						
A1 00111710E.	_	Chaves N.M.						
AT TOP PROD. I		14. API NO.						
		30-005-61041						
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD)						
REPORT, OR OT	HER DAIR	3788 GL, 3793 KB						
REQUEST FOR APPR	OVAL TO: SUBSEQUENT REPORT OF:	3700 CE, 3770 3E						
TEST WATER SHUT-								
FRACTURE TREAT		מלאלול אולי לייני						
SHOOT OR ACIDIZE								
REPAIR WELL PULL OR ALTER CA	sing DOT	or Form 9-330)						
MULTIPLE COMPLET		1 1981						
CHANGE ZONES								
ABANDON*	GAS GICAL SURVEY							
(other) Casing	ROSWELL, N	NEW WEXICO						
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*								
9-7-81	Ran 150 joints 7" 23# casing, set in cement at 4962' w/325 sacks Self Stress, 3% CaCl ₂ . WOC 18 hrs. Pressure up 1000# for 30 minutes logging no pressure decrease.							
9-27-81	TD 6290'.							
9-28-81	Set 40 sack plug at 5520' to 5420 to 4900'. Prep to perforate interest	and 60 sack plug at 5000' rval from 4376-4414'.						

Subsurface Safety Valve: Manu. and Type						Set @	Ft.
18. I herel	Sentry that the	CHAPMAN	rue and correct	President	DATE	9-29-81	
APPROVED	OCT	E 1981 BIONE SURV	(This space forTITLE	Federal or State office	e use) DATE _		