

NM OIL CONS. COMMISSION  
Dr. r. DP  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL. ATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-14294

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

PZ Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat 11.4.1981

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 7- T9S-R26E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

SEP 16 1981

2. NAME OF OPERATOR

McClellan Oil Corporation ✓

O. C. D.

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell N.M. 88201

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1250' FSL & 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3720' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Casing & Cementing ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/1/81 Drilled 40 foot with 17 1/2" bit and ran 40' 14" casing conductor pipe.  
Cemented with 6 yards ready-mix.

9/2/81 Move in Tex-Mex rig #2

9/7/81 Drilled to 855' with 12 1/4" bit. Ran 853' of 8 5/8" 23 lb/ft casing.  
Cemented with 200 sacks Halliburton Light cement w/2% CaCl<sub>2</sub> and 1/4 lb/sk flocele and 200 sacks Class C w/2% CaCl<sub>2</sub>. Plug down at 6:00 p.m.  
Did not circulate cement. WOC 6 hours. Ran temperature survey: TOC-130'.  
One inched casing with 125 sacks of Class C Thixset w/2% CaCl<sub>2</sub>. Circulated cement.  
WOC 8 hours. Tested casing to 500 PSI for 30 minutes.  
Resume drilling with 7 7/8" bit.

SEP 9 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Karl Kuykendall

TITLE Engineer

DATE 9-8-81

(This space for Federal or State office use)

APPROVED BY ROGER A. CHAPMAN  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

SEP 14 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side